

# Content

<b>Index of tables .....</b>	<b>26</b>
<b>Index of figures .....</b>	<b>31</b>
<b>1. Scope .....</b>	<b>51</b>
<b>2. Overview .....</b>	<b>53</b>
<b>2.1 Objectives .....</b>	<b>53</b>
<b>2.2 Scientific potential of a 100-m class telescope .....</b>	<b>54</b>
<b>2.3 Context.....</b>	<b>58</b>
<b>2.4 The OWL concept .....</b>	<b>60</b>
2.4.1 The history of telescope growth.....	60
2.4.2 A giant telescope in an industrial context.....	61
<b>2.5 Top level requirements.....</b>	<b>62</b>
<b>2.6 Design overview.....</b>	<b>64</b>
2.6.1 Telescope optics .....	65
2.6.2 Structural design.....	71
2.6.3 A controlled opto-mechanical system .....	73
2.6.4 Enclosure, open air operation .....	78
2.6.5 Instrumentation .....	80
<b>2.7 Progressive implementation.....</b>	<b>83</b>
<b>2.8 Observatory operation .....</b>	<b>85</b>
<b>2.9 Site considerations.....</b>	<b>86</b>
<b>2.10 Plans for final design and construction .....</b>	<b>88</b>

<b>2.11</b>	<b>Cost estimate.....</b>	<b>91</b>
<b>2.12</b>	<b>The ELT Design Study.....</b>	<b>93</b>
<b>2.13</b>	<b>Scalability.....</b>	<b>95</b>
2.13.1	Science.....	95
2.13.2	Requirements.....	96
2.13.3	Concept design.....	97
2.13.4	Cost and schedule.....	98
<b>2.14</b>	<b>Risk areas.....</b>	<b>99</b>
2.14.1	Environmental risks.....	100
2.14.2	System risks.....	102
2.14.3	Risk management.....	107
<b>3.</b>	<b>Science case.....</b>	<b>109</b>
<b>3.1</b>	<b>Introduction.....</b>	<b>109</b>
<b>3.2</b>	<b>Science with OWL.....</b>	<b>110</b>
3.2.1	OWL performance.....	111
3.2.1.1	Confusion about confusion.....	111
3.2.1.2	Étendue, or the AΩ product.....	111
3.2.1.3	Signal-to-noise vs diameter D.....	111
3.2.1.4	The power of a 100m telescope.....	112
3.2.1.5	The wavelength range.....	114
3.2.2	The highlight science cases.....	116
3.2.2.1	Terrestrial Planets In Extra-Solar Systems.....	116
3.2.2.2	Resolved Stellar Populations in a representative sample of the Universe.....	118
3.2.2.3	The First Objects And Re-ionization Structure Of The Universe.....	118
3.2.2.3.1	The highest Redshift Galaxies.....	118
3.2.2.3.2	Galaxies at the end of Re-ionization.....	119
3.2.2.3.3	Probing the universe during the re-ionization epoch.....	120
<b>3.3</b>	<b>Requirements from the science case.....</b>	<b>121</b>
<b>4.</b>	<b>Top level requirements.....</b>	<b>127</b>
<b>4.1</b>	<b>Introduction.....</b>	<b>127</b>
<b>4.2</b>	<b>Overall requirements.....</b>	<b>127</b>
4.2.1	The OWL telescope.....	127
4.2.2	The Conceptual Design (Phase A).....	128
4.2.3	Evolution of the Top Level requirements.....	128
4.2.4	Operational lifetime.....	128
4.2.5	Location of OWL.....	128
4.2.6	Optical design.....	128

4.2.7	Maintenance .....	129
4.2.8	Instrumentation .....	129
4.2.9	Coating optimization .....	129
4.2.10	Astronomical site monitor .....	129
4.2.11	Safety .....	129
<b>4.3</b>	<b><i>Performance requirements</i></b> .....	<b>129</b>
4.3.1	Telescope transmission .....	130
4.3.2	Emissivity .....	130
4.3.3	Sky coverage .....	130
4.3.4	Image quality .....	130
4.3.4.1	Telescope .....	130
4.3.4.2	Adaptive Optics .....	130
4.3.4.2.1	Telescope AO .....	131
4.3.4.2.2	Single Conjugate AO .....	131
4.3.4.2.3	Multi Conjugate AO .....	131
4.3.4.2.4	Ground Layer AO .....	132
4.3.4.2.5	Multi-Object AO .....	132
4.3.4.2.6	Extreme AO .....	132
4.3.4.2.7	AO at optical wavelengths .....	133
4.3.4.2.8	Laser Guide Stars .....	133
4.3.5	Atmospheric dispersion compensation .....	133
4.3.6	Atmospheric refraction .....	133
<b>5.</b>	<b>System Engineering</b> .....	<b>135</b>
<b>5.1</b>	<b><i>Level 1 requirements</i></b> .....	<b>135</b>
<b>5.2</b>	<b><i>Design constraints and guidelines</i></b> .....	<b>137</b>
<b>5.3</b>	<b><i>Complex Systems, methods and modelling</i></b> .....	<b>138</b>
5.3.1	Complex System .....	138
5.3.2	Methods .....	139
5.3.2.1	Science and Engineering .....	139
5.3.2.1.1	System Design .....	140
5.3.2.1.1.1	Top Level Requirements .....	140
5.3.2.1.1.2	System Requirements Management .....	140
5.3.2.1.1.3	Functional Analysis .....	141
5.3.2.1.1.4	Logical Architecture Definition .....	142
5.3.2.1.2	Physical Design & Manufacturing .....	143
5.3.2.1.2.1	Physical Design .....	144
5.3.2.1.2.2	Manufacturing .....	144
5.3.2.1.3	System Integration .....	144
5.3.2.2	Tools .....	145
5.3.3	Modelling .....	145
5.3.3.1.1	Modelling Approach .....	145

5.3.3.1.2	Architecture Concept .....	148
5.3.3.2	DOORS Model, System requirements management .....	151
<b>5.4</b>	<b><i>Disturbances Characterization</i></b> .....	<b>152</b>
5.4.1	Environment.....	152
5.4.1.1	Wind .....	152
5.4.1.1.1	Wind characterization from literature .....	152
5.4.1.1.1.1	Wind Velocity, integral length and turbulence intensity Profiles .....	152
5.4.1.1.1.2	Power Spectral Density .....	153
5.4.1.1.2	Computational Fluid Dynamics (CFD) .....	155
5.4.1.1.3	Full scale measurements .....	157
5.4.1.1.4	Wind tunnel measurements .....	158
5.4.1.2	Atmospheric turbulence (AO) .....	159
5.4.1.3	Temperature, humidity, rain, snow, ice, dust, radiation .....	161
5.4.1.4	Microseismicity .....	164
5.4.2	System Induced Disturbances .....	164
5.4.3	Human induced disturbance .....	164
5.4.3.1	Camp, hotel, sewage, transport, etc.....	164
5.4.3.2	Power generation .....	164
5.4.3.3	Light pollution .....	165
5.4.4	Survival load case of the opto-mechanical elements .....	165
5.4.4.1	Earthquake .....	165
5.4.4.2	Wind .....	166
5.4.4.3	Temperature .....	167
<b>5.5</b>	<b><i>Error budgets</i></b> .....	<b>167</b>
<b>5.6</b>	<b><i>Reliability, Availability, Maintainability, Safety (RAMS)</i></b> .....	<b>180</b>
5.6.1	Product Assurance Roles & Responsibilities .....	180
5.6.2	Safety.....	180
5.6.2.1	General.....	180
5.6.2.2	Safety Assurance Program and organization.....	181
5.6.2.3	Safety assurance activities.....	181
5.6.3	Reliability and Maintainability.....	181
5.6.3.1	Failure Tolerance .....	181
5.6.3.2	Single point failure list .....	181
5.6.3.3	Reliability and Maintainability Data File.....	181
5.6.3.3.1	Reliability Engineering .....	182
5.6.3.3.1.1	Reliability Analyses.....	182
5.6.3.3.2	Maintainability Engineering.....	182
5.6.3.3.2.1	Establishment of Maintainability Requirements.....	182
5.6.3.3.2.2	Maintainability Inputs to Maintenance Plan .....	183
5.6.3.3.2.3	Maintainability Analyses .....	183
5.6.3.3.2.4	Maintainability Demonstration .....	183
5.6.4	Conclusion – OWL Dependability Objective Sheet .....	184

<b>6.</b>	<b>Telescope optics .....</b>	<b>185</b>
6.1	<b>Requirements and guidelines.....</b>	<b>185</b>
6.2	<b>Optical design .....</b>	<b>188</b>
6.2.1	Design trade-off .....	188
6.2.2	Baseline design .....	194
6.2.3	Optional corrector .....	198
6.2.4	Reduced aperture designs.....	198
6.2.5	Future design iterations .....	201
6.3	<b>Optical characteristics .....</b>	<b>202</b>
6.3.1	Nominal optical quality.....	202
6.3.2	Vignetting.....	206
6.3.3	Stray light and baffling .....	207
6.3.4	Emissivity.....	208
6.3.5	Sensitivity analysis.....	209
6.3.6	Imaging of turbulent layers.....	213
6.3.7	Imaging of Laser Guide Stars .....	216
6.4	<b>Diffraction and high contrast imaging.....</b>	<b>218</b>
6.4.1	Diffraction.....	218
6.4.1.1	Structure of PSF in diffraction-limited regime.....	218
6.4.1.1.1	Pupil modelling elements .....	218
6.4.1.1.2	Secondary mirror support.....	220
6.4.1.1.3	“Missing” segments .....	220
6.4.1.1.4	Ropes .....	221
6.4.1.1.5	Diffraction by the gaps.....	221
6.4.1.2	PSF representation: intensity slices .....	223
6.4.1.3	Effects of phasing errors on the PSF .....	224
6.4.1.3.1	Diffraction associated to piston and tip-tilt.....	224
6.4.1.3.2	Intensity slice representation (FoV=1", $\lambda=650\text{nm}$ ) .....	224
6.5	<b>Optics design and fabrication .....</b>	<b>226</b>
6.5.1	Segments.....	226
6.5.1.1	Segment size and distribution .....	227
6.5.1.2	Segments thermo-mechanical properties .....	229
6.5.1.3	Segments substrates .....	230
6.5.1.4	Segments polishing.....	236
6.5.1.5	Segments supports .....	240
6.5.2	Corrector optics .....	241
6.6	<b>Safety .....</b>	<b>245</b>
<b>7.</b>	<b>Non-adaptive wavefront control .....</b>	<b>247</b>
7.1	<b>Requirements.....</b>	<b>247</b>

<b>7.2</b>	<b>General control architecture</b> .....	<b>248</b>
7.2.1	Wind rejection .....	251
7.2.2	Friction compensation.....	256
7.2.3	Field stabilization .....	260
<b>7.3</b>	<b>Pre-alignment</b> .....	<b>263</b>
<b>7.4</b>	<b>Active optics</b> .....	<b>265</b>
7.4.1	Introduction .....	265
7.4.2	Alignment of the segments in M1 and M2.....	265
7.4.3	Correction of mirror deformations .....	266
7.4.4	Correction of the rigid-body alignment of the mirrors .....	268
7.4.5	Relationship between various types of aberrations.....	269
7.4.6	Operation with adaptive optics .....	269
<b>7.5</b>	<b>Phasing</b> .....	<b>270</b>
7.5.1	Phasing strategy .....	270
7.5.2	Blind phasing .....	270
7.5.3	Position sensors .....	271
7.5.4	On-sky calibrations .....	271
7.5.4.1	Optical Phasing .....	271
7.5.4.2	On-sky phasing techniques - overview.....	271
7.5.4.2.1	Modified Shack-Hartmann technique.....	271
7.5.4.2.2	Modified Mach-Zehnder technique .....	272
7.5.4.2.3	Phase filtering technique .....	273
7.5.4.2.4	Diffraction image technique .....	274
7.5.4.2.5	Pyramid technique .....	275
7.5.4.2.6	CCD.....	275
7.5.4.3	Open loop performance.....	276
7.5.4.3.1	The optical signal.....	276
7.5.4.3.2	The CCD images .....	276
7.5.4.3.3	Signal analysis.....	277
7.5.4.3.4	Results.....	278
7.5.4.3.5	Increase of the capture range.....	279
7.5.4.3.6	Calibration.....	279
7.5.4.4	Identification of the borders .....	280
7.5.4.5	Closed-loop results.....	280
7.5.4.6	Phasing OWL .....	281
7.5.4.6.1	Phasing of one petal .....	281
7.5.4.6.2	Phasing of the petals .....	285
7.5.4.6.3	Measurements under aberrations.....	285
7.5.4.6.4	Disentangling M1&M2.....	285
7.5.5	Control of segmented mirrors (M1 & M2).....	286
<b>7.6</b>	<b>Active Phasing Experiment (APE)</b> .....	<b>295</b>
7.6.1	Opto-mechanical design .....	295

7.6.2	Internal Metrology .....	297
7.6.3	The Phasing WaveFront Sensor Module .....	297
7.6.4	Schedule and observations.....	297

## **8. Adaptive Optics..... 299**

### **8.1 Introduction ..... 299**

### **8.2 First generation Adaptive Optics ..... 299**

8.2.1	Single Conjugate Adaptive Optics .....	300
8.2.1.1	Performance requirements.....	301
8.2.1.2	Implementation Concept.....	303
8.2.1.2.1	M6 Adaptive Mirror unit .....	303
8.2.1.2.2	Visible wavefront sensor unit.....	306
8.2.1.2.3	Infrared Pyramid WFS.....	309
8.2.1.2.4	Real Time Computer (RTC) .....	312
8.2.1.3	Predicted performance.....	313
8.2.1.3.1	Visible Shack Hartmann wavefront sensor.....	313
8.2.1.3.2	Infrared Pyramid Wavefront sensor.....	314
8.2.1.3.3	Performance at 10 microns and beyond .....	316
8.2.1.3.4	Effect of the outer scale of turbulence on performance.....	317
8.2.1.4	Near-Term development plan .....	318
8.2.1.4.1	Modelling and Simulation .....	318
8.2.1.4.2	AO Concept and design .....	319
8.2.1.4.3	AO key elements status and development.....	321
8.2.1.4.4	Testing a large DM in closed loop .....	334
8.2.1.4.5	Detectors for wavefront sensors.....	336
8.2.1.4.6	Real Time Computer .....	337
8.2.2	Ground Layer Adaptive Optics.....	342
8.2.2.1	Performance requirements.....	344
8.2.2.2	Implementation Concept.....	346
8.2.2.2.1	Corrector and wavefront sensors .....	346
8.2.2.2.2	Control and Real Time Computer.....	346
8.2.2.3	Predicted performance.....	348
8.2.2.3.1	Sky coverage.....	348
8.2.2.4	Near-Term development plan .....	352
8.2.2.4.1	Modelling and Simulation .....	352
8.2.2.4.2	AO concept and design .....	352
8.2.2.4.3	AO key component status and development.....	353
8.2.3	Distributed Multi Object Adaptive Optics.....	354
8.2.3.1	Implementation Concept.....	356
8.2.3.1.1	Overview.....	356
8.2.3.1.2	Wavefront sensor .....	357
8.2.3.1.3	Micro deformable mirror .....	357
8.2.3.1.4	Control and Real Time computer .....	358

8.2.3.2	Predicted performance .....	360
8.2.3.3	Near-Term development plan .....	361
8.2.3.3.1	Modelling and Simulation .....	362
8.2.3.3.2	AO Concept and design .....	362
8.2.3.3.3	AO key component status and development .....	363
<b>8.3</b>	<b><i>Second generation Adaptive Optics .....</i></b>	<b>363</b>
8.3.1	Multi Conjugate Adaptive Optics .....	364
8.3.1.1	Performance requirements .....	365
8.3.1.2	Implementation Concept .....	366
8.3.1.2.1	Corrective elements .....	366
8.3.1.2.2	Wavefront sensors .....	367
8.3.1.2.3	MCAO control .....	367
8.3.1.2.4	Real Time Computer .....	367
8.3.1.3	Predicted performance .....	368
8.3.1.3.1	MCAO sky coverage .....	368
8.3.1.3.2	Simulation Results .....	369
8.3.1.4	Mid-Term development plan .....	373
8.3.1.4.1	Modelling and Simulation .....	373
8.3.1.4.2	MCAO design .....	373
8.3.1.4.3	MCAO calibration issues .....	374
8.3.1.4.4	AO key component status and development .....	375
8.3.2	Extreme Adaptive Optics and High Contrast Imaging: EPICS project .....	381
8.3.2.1	EPICS Top level performance requirements .....	381
8.3.2.2	EPICS Adaptive Optics concept .....	381
8.3.2.2.1	Common path system: .....	382
8.3.2.2.2	Individual Channel paths .....	384
8.3.2.3	Coronagraphy .....	384
8.3.2.4	Correction of co-phasing errors .....	386
8.3.2.5	EPICS performance .....	388
8.3.2.6	Technological requirements for EPICS .....	389
8.3.2.7	Future development plan .....	390
<b>8.4</b>	<b><i>Third generation Adaptive Optics .....</i></b>	<b>392</b>
8.4.1	Introduction .....	392
8.4.2	Toward the 3 <sup>rd</sup> generation AO systems with LGSs .....	392
8.4.2.1	From Single Conjugate to Laser Tomography AO .....	392
8.4.2.2	Laser assisted Ground Layer Adaptive Optics .....	393
8.4.2.3	Laser Assisted Multi-Conjugate Adaptive Optics .....	394
8.4.2.4	Laser Assisted Multi-Object Adaptive Optics .....	395
8.4.3	ELTs and LGSs issues .....	395
8.4.4	Potential solutions to LGS issues .....	397
8.4.4.1	Spot Elongation .....	397
8.4.4.2	Spot aberrations .....	397
8.4.4.3	Fratricide effect .....	398
8.4.5	New Laser Guide Star concepts .....	398



8.4.5.1	Pseudo Infinite Guide Stars .....	398
8.4.5.2	Sky Projected Laser Array Shack-Hartmann .....	399
8.4.5.3	Virtual Wavefront Sensor .....	399
8.4.5.4	Variable Wavefront Sensors .....	400
8.4.5.5	Laser Guided AO with on-sky phase shifting Interferometry .....	401
8.4.6	Strategies of the LGS program for OWL .....	404
8.4.6.1	Background .....	404
8.4.6.2	Status and planned tasks .....	404

## **9. Telescope structure and kinematics ..... 407**

### **9.1 Design Principles..... 407**

### **9.2 Design Assumption ..... 409**

### **9.3 Design Evolution..... 409**

9.3.1	1997 Design.....	411
9.3.2	1998 Design.....	411
9.3.3	1999 Design.....	412
9.3.4	2000 Design.....	414
9.3.5	2002 Design.....	414
9.3.6	2004 Design.....	415
9.3.7	2005 Design (current baseline).....	416

### **9.4 Conceptual Design ..... 416**

9.4.1	Structural design.....	417
9.4.1.1	Material selection .....	417
9.4.1.2	Structural element selection.....	418
9.4.2	Fractal Design.....	419
9.4.2.1	Base module .....	419
9.4.3	Azimuth Structure.....	420
9.4.4	Altitude Structure.....	421
9.4.4.1	Primary mirror obscuration.....	423
9.4.4.2	Structural ropes.....	423
9.4.4.2.1	Material selection.....	424
9.4.4.2.2	Wind on ropes .....	425
9.4.4.3	Focal Stations .....	426
9.4.4.3.1	Alternative focal station.....	427
9.4.5	Sub-Systems design.....	428
9.4.5.1	Kinematics.....	428
9.4.5.1.1	Torque requirement.....	428
9.4.5.1.2	Acceleration.....	428
9.4.5.1.3	Friction Drive & Bearing.....	428
9.4.5.1.4	Hydrostatic pads and direct drive.....	434
9.4.5.1.5	Magnetic Levitation.....	435
9.4.5.2	Corrector.....	437

9.4.5.3	M3 and M4 Unit .....	438
9.4.5.4	M5 Unit .....	438
9.4.5.5	M6 Unit .....	438
9.4.5.5.1	Interface to the corrector.....	439
9.4.5.5.2	M6 Unit design volume .....	439
9.4.6	Segments support system. ....	440
9.4.6.1	Segment assembly.....	441
9.4.6.2	Extractors.....	441
9.4.6.3	Position Actuators characteristics.....	442
9.4.6.3.1	Axial stiffness.....	442
9.4.6.3.2	Load cases.....	442
9.4.6.3.3	Accuracy.....	442
9.4.6.3.4	Stroke .....	442
9.4.6.3.5	Closed Loop Bandwidth.....	443
9.4.6.3.6	Maximum tracking rate .....	443
9.4.6.3.7	Maximum slewing rate.....	443
9.4.6.3.8	Heat dissipation.....	444
9.4.7	Wind Evaluation Breadboard .....	444
9.4.7.1	WEB layout.....	444
9.4.8	Internal Metrology .....	446
9.4.9	Thermal control and design provision .....	446
9.4.9.1	Thermally controlled volumes.....	446
9.4.9.2	Passive thermal control of the mechanical steel structure.....	447
9.4.10	Safety.....	447
9.4.11	Mass & Moment breakdown.....	448
<b>9.5</b>	<b>Structural analysis .....</b>	<b>448</b>
9.5.1	Analysis tree .....	450
9.5.2	Static Analysis .....	451
9.5.2.1	Gravity.....	452
9.5.2.2	Steady State Wind.....	453
9.5.3	Thermal analysis.....	454
9.5.4	Dynamic Analysis.....	458
9.5.4.1	Modal.....	458
9.5.4.2	Dynamic Wind Load .....	463
9.5.4.2.1	Macro scale wind effect on segmented mirrors .....	464
9.5.4.2.2	Micro scale wind effect on phasing error .....	467
9.5.4.3	Effect of soil and foundation .....	469
9.5.5	Safety Analysis .....	471
9.5.5.1	Wind .....	471
9.5.5.2	Earthquake .....	472
9.5.5.3	Buckling.....	472
9.5.5.4	Fatigue .....	473
9.5.5.5	Pretension of ropes .....	474
<b>9.6</b>	<b>Structure design Options .....</b>	<b>475</b>

9.6.1	Base line High configuration (2005 design) .....	475
9.6.2	Glass Ceramic low configuration .....	475
9.6.3	SiC high and low configurations.....	476
9.6.4	Glass Ceramic 60 m configuration .....	477
<b>10.</b>	<b>Adapter-Rotator.....</b>	<b>479</b>
10.1	<i>Requirements</i> .....	479
10.2	<i>Constraints</i> .....	480
10.3	<i>Notional Design</i> .....	481
10.3.1	Pick-up mirrors.....	482
10.4	<i>Adapter-Rotator configuration vs instruments and functions</i> .....	483
<b>11.</b>	<b>Enclosure and infrastructures .....</b>	<b>485</b>
11.1	<i>Telescope enclosure</i> .....	485
11.1.1	Baseline design description .....	487
11.1.2	Concrete works .....	495
11.1.3	Structure and mechanisms .....	497
11.1.4	Alternatives .....	501
11.2	<i>Infrastructures</i> .....	506
11.2.1	Mirrors maintenance .....	508
11.2.2	Laboratories .....	509
11.2.3	Control room and personnel offices .....	510
11.2.4	Air conditioning and chilled water plants .....	510
11.2.5	Fluid distribution.....	511
11.2.6	Power station .....	511
11.2.7	Personnel accommodation building .....	512
11.2.8	Site preparation .....	512
11.2.8.1	Camp and first infrastructures .....	513
11.2.8.2	Earth works for telescope platform.....	513
11.2.8.3	Access roads to the Observatory .....	515
11.2.8.4	Miscellaneous .....	516
<b>12.</b>	<b>Instrumentation .....</b>	<b>517</b>
12.1	<i>Technical instrumentation</i> .....	517
12.2	<i>Science instrumentation</i> .....	518
12.2.1	Scope of the instrument concept studies .....	518
12.2.2	Instrument Concept Studies.....	519
12.2.3	CODEX: high resolution. ultra-stable VIS-R spectrograph.....	519

12.2.3.1	QuantEYE .....	523
12.2.3.2	Hyper-telescope NIR camera .....	526
12.2.3.3	ONIRICA: OWL NIR Imaging Camera .....	527
12.2.3.4	MOMFIS: Multi Object. Multi Field Near –IR Spectrograph.....	534
12.2.3.5	EPICS: Exo- Planet Imaging Camera Spectrograph.....	537
12.2.3.5.1	Science drivers .....	538
12.2.3.5.2	Targets.....	538
12.2.3.5.3	Top level requirements .....	539
12.2.3.5.3.1	Instrument. general.....	539
12.2.3.5.3.2	Instrument main observing modes and performance requirements .....	540
12.2.3.5.3.3	Requirements to the site . the telescope and observing time.....	541
12.2.3.5.4	InstrumentConcept .....	541
12.2.3.5.5	Adaptive optics .....	542
12.2.3.5.6	Coronagraphy .....	543
12.2.3.5.7	Instruments .....	543
12.2.3.5.7.1	Differential Imager .....	543
12.2.3.5.7.2	Integral Field Spectrograph .....	544
12.2.3.5.7.3	Differential Polarimeter .....	544
12.2.3.5.8	Integration times for a 5 $\sigma$ detection in case of background limited observation.....	545
12.2.3.5.9	Need for 100m .....	548
12.2.3.5.10	Systematic Errors .....	548
12.2.3.5.11	Technological requirements for EPICS.....	548
12.2.3.6	T-OWL: Mid-Infrared Imager .....	549
12.2.3.7	SCOWL : Imager at Submillimeter Camera at OWL .....	553
12.2.4	Versatile Instruments and Dedicated Experiments or Surveys .....	557
12.2.5	Telescope Interface and Deployment Considerations.....	557
12.2.6	Adaptive Optics Requirement Overview .....	559
12.2.7	Detector Requirement Overview.....	559

## **13. Transport and integration ..... 561**

### **13.1 Transport..... 561**

13.1.1	Design provisions.....	561
13.1.1.1	Mechanics .....	561
13.1.1.2	Optics .....	562

### **13.2 Site integration ..... 562**

13.2.1	Design provisions.....	563
13.2.1.1	Mechanics .....	563
13.2.1.2	Alignment metrology.....	563
13.2.1.3	Telescope truss structure integration .....	564
13.2.1.3.1	Phase 1.....	564
13.2.1.3.2	Phase 2.....	565
13.2.1.3.3	Phase 3.....	565
13.2.1.3.4	Phase 4.....	566

13.2.1.3.5	Phase 5 .....	567
13.2.1.3.6	Phase 6 .....	567
13.2.1.3.7	Phase 7 .....	568
13.2.1.4	Segment integration .....	569
13.2.1.4.1	Segment handling tool .....	570
13.2.1.5	Optics .....	573
13.2.1.5.1	Initial alignment .....	573
13.2.2	Safety .....	574

## **14. Site Characterisation ..... 575**

### **14.1 Introduction ..... 575**

14.1.1	Instrumentation and methods .....	575
14.1.1.1	Cloudiness .....	575
14.1.1.2	Precipitable Water Vapor .....	576
14.1.1.3	Aerosol Extinction .....	576
14.1.1.4	Seeing .....	576
14.1.1.5	Turbulence Vertical Profiles .....	576
14.1.1.6	Turbulence Outer Scale .....	577
14.1.1.7	Wave front coherence time .....	577

### **14.2 Parameters space ..... 577**

14.2.1	General astronomy .....	577
14.2.1.1	Cloudiness .....	577
14.2.1.2	Precipitable water vapour .....	578
14.2.1.3	Aerosol Extinction .....	581
14.2.1.3.1	Saharan dust .....	581
14.2.1.3.2	Contrails .....	582
14.2.1.4	Sky background .....	583
14.2.1.5	Seeing .....	584
14.2.2	Telescope design & operation .....	585
14.2.2.1	Wind, temperature and humidity .....	585
14.2.2.2	Seismicity .....	585
14.2.2.3	Topology, soil characteristics .....	586
14.2.2.4	Infrastructures .....	587
14.2.3	AO observations .....	588
14.2.3.1	Lower atmosphere turbulence and wind .....	588
14.2.3.2	Higher atmosphere turbulence and wind .....	590
14.2.3.3	Full Atmospheric profiles .....	591
14.2.3.4	Sodium layer .....	593

### **14.3 Site selection strategy ..... 593**

14.3.1	Identification of potential candidates .....	593
14.3.2	Characterization of the parameter space .....	597
14.3.3	Analysis of climate stability .....	598
14.3.3.1	The experience of ESO Observatory .....	598

14.3.3.2	FRIOWL .....	599
<b>14.4</b>	<b>Site preservation and monitoring.....</b>	<b>602</b>
14.4.1	Local Seeing control .....	602
14.4.2	Astronomical Site Monitoring Station .....	603
<b>15.</b>	<b>Maintenance and operations .....</b>	<b>607</b>
<b>15.1</b>	<b>Maintenance .....</b>	<b>607</b>
15.1.1	Design provisions.....	607
15.1.1.1	Human access and handling.....	607
15.1.1.1.1	Human access .....	607
15.1.1.1.2	Handling Facilities.....	608
15.1.1.2	Corrector Handling .....	609
15.1.1.3	M6 Unit Handling .....	610
15.1.1.4	Primary mirror covers handling .....	611
15.1.1.4.1	Covers Docking and undocking operations. ....	612
15.1.1.5	Sliding Enclosure.....	613
15.1.1.6	Secondary mirror handling .....	614
15.1.2	Safety.....	615
<b>15.2</b>	<b>Observatory operations.....</b>	<b>615</b>
<b>15.3</b>	<b>Science operations .....</b>	<b>617</b>
<b>16.</b>	<b>Management .....</b>	<b>619</b>
<b>16.1</b>	<b>Introduction .....</b>	<b>619</b>
<b>16.2</b>	<b>Programme organization.....</b>	<b>622</b>
<b>16.3</b>	<b>Programme management and control .....</b>	<b>627</b>
<b>16.4</b>	<b>Programme team.....</b>	<b>628</b>
<b>16.5</b>	<b>Programme phases.....</b>	<b>629</b>
<b>16.6</b>	<b>Schedule .....</b>	<b>630</b>
<b>16.7</b>	<b>Cost of the programme.....</b>	<b>632</b>
16.7.1	Cost estimate methodology .....	632
16.7.2	Cost .....	632
16.7.3	Staffing.....	633
16.7.3.1	Design phase .....	633
16.7.3.2	Construction phase .....	633
16.7.3.3	Operations phase .....	633
	<b>Design parameters – Summary .....</b>	<b>634</b>

<b>References .....</b>	<b>641</b>
<b>Acknowledgements .....</b>	<b>649</b>
<b>Contributors .....</b>	<b>652</b>
<b>Appendix 1. The ELT Design Study .....</b>	<b>655</b>
<i>A-1.1 Work Packages .....</i>	<i>655</i>
<i>A-1.2 Wavefront control .....</i>	<i>660</i>
<i>A-1.3 Optical fabrication .....</i>	<i>666</i>
<i>A-1.4 Mechanics.....</i>	<i>667</i>
<i>A-1.5 Enclosure &amp; wind studies.....</i>	<i>669</i>
<i>A-1.6 Adaptive Optics.....</i>	<i>669</i>
<i>A-1.7 Operations .....</i>	<i>670</i>
<i>A-1.8 Instrumentation.....</i>	<i>670</i>
<i>A-1.9 Site characterization.....</i>	<i>671</i>
<i>A-1.10 Integrated modelling.....</i>	<i>672</i>
<b>Appendix 2. ELT Design Study Participants.....</b>	<b>673</b>
<b>Appendix 3. System status at construction readiness review ..</b>	<b>677</b>
<b>Appendix 4. Phase B Schedule estimate .....</b>	<b>683</b>
<b>Appendix 5. Phase C/D schedule estimate .....</b>	<b>689</b>
<b>Appendix 6. Cost estimate.....</b>	<b>703</b>
<b>Appendix 7. Software tools .....</b>	<b>707</b>
<b>Appendix 8. Optical design – criteria and merit function .....</b>	<b>711</b>
<b>Appendix 9. Optional corrector.....</b>	<b>715</b>

# Index of tables

Table 2-1 Summary of top level requirements .....	63
Table 2-2. Baseline design, optical characteristics. ....	65
Table 2-3. Segments characteristics. ....	69
Table 2-4 Instrument Concept Studies .....	81
Table 2-5. Subsystems status at start of segments integration. ....	84
Table 2-6. OWL cost estimate, capital investment. ....	92
Table 2-7 Summary of exo-planet capability as a function of ELT size .....	95
Table 2-8 Summary of studies of resolved stellar populations as a function of ELT size .....	96
Table 2-9 Summary of studies of the high-redshift Universe as a function of ELT size .....	96
Table 2-10. Dependence of main telescope requirements on diameter D .....	97
Table 2-11. Summary of environmental risks (a few comments still to be incorporated). ....	101
Table 2-12. System risks .....	103
Table 2-13. Areas of Risk Impact. ....	108
Table 3-1. Primary science cases .....	110
Table 3-2. (From Science Book) Gains in magnitude for the same signal-to-noise and exposure time when observing unresolved sources in the background-limited regime. The gains are shown relative to an 8m telescope delivering 0.5" images. ....	113
Table 3-3. (from [118]) IR performance of several ELTs compared to that of the JWST space telescope, in terms of the point source sensitivity ratio ELT/JWST. In the near-infrared an ELT outperforms a 6.5m cold (~30K) space telescope such as JWST (bold font shows ratio > 0.5). ....	114
Table 3-4. Diffraction limit (Res, in milliarcsecond) and corresponding limiting magnitudes for various telescope sizes, under identical conditions and assumptions (i.e. same Strehl ratio of 50%, efficiency 30%, sky background from Paranal, no atmospheric extinction). While the absolute values may change with assumptions, the relative ones should not. ....	115
Table 3-5. Summary of the capabilities of a sub-mm instrument on OWL compared to those of ALMA. ....	116
Table 3-6. Science requirements. S stands for Strehl ratio .....	121
Table 3-7 Requirements from the main science cases (adapted from Hook [120]) .....	126
Table 4-1. Single conjugate AO requirements. ....	131
Table 4-2. Multi-conjugate AO requirements .....	132



Table 4-3. Ground-layer AO requirements..... 132

Table 4-4 Multi Object AO requirements..... 132

Table 4-5. Extreme AO requirements. .... 132

Table 4-6. AO requirements at optical wavelengths (provisional). .... 133

Table 4-7. Effect of differential displacement due to atmospheric refraction between meridian and one hour from meridian. RA and DEC are right ascension and declination, Sep is the separation between the stars, Displ is the relative differential displacement in milliarcsec at one hour from meridian, and ΔT is the maximum exposure time in minutes to have a displacement < 10% of the diffraction peak. .... 134

Table 5-1. Image quality requirements, non-adaptive modes..... 136

Table 5-2. Image quality requirements, with first and second generation adaptive optics. .... 137

Table 5-3. Failure / damage hierarchy and allowable rate of occurrence..... 137

Table 5-4. Structural subsystem. .... 149

Table 5-5. Optic model, inputs and outputs. .... 149

Table 5-6. Control loops..... 150

Table 5-7. Integrated Model - Intermediate steps..... 150

Table 5-8. Integrated Model validation methods..... 151

Table 5-9: Typical expected median values of the atmospheric turbulence parameters based on the experience at existing observatories. .... 161

Table 5-10: Various environmental conditions on Paranal. .... 162

Table 5-11: Temperature conditions on Paranal..... 164

Table 5-12: Earthquake characteristics for two different sites. .... 166

Table 5-13: Survival wind speed for telescope and enclosure structure. .... 167

Table 5-14: Survival temperature conditions for the telescope and enclosure structure..... 167

Table 5-15. Image quality budget - main positions. .... 169

Table 5-16. OWL Image quality budget in SCAO mode. .... 170

Table 6-1. Optical design: guidelines and objectives. M=Mandatory; C=Critical; D=Desirable. 186

Table 6-2. Ratings for designs No 1 to 4. (\*) P=Pass; F=Fail..... 193

Table 6-3. Baseline design, optical prescription. .... 197

Table 6-4. 4-mirror f/15 design, 60-m aperture; optical prescription..... 199

Table 6-5. 4-mirror f/15, 60-m aperture design. Nominal optical quality..... 199

Table 6-6. Baseline design, optical quality..... 202

Table 6-7. Expected emissivity at 2.2 μm, classical Al or Au coatings. .... 208

Table 6-8. Expected emissivity at 2.2 μm, Gemini enhanced Ag coatings. .... 208

Table 6-9. Baseline design, sensitivity matrix. .... 211

Table 6-10. Baseline design, sensitivity matrix, corrector decenters (rigid body)..... 212

Table 6-11. Segments characteristics..... 227

Table 6-12. Compared performance of Zerodur, fused silica and silicon carbide with respect to through-thickness CTE and thermal gradients (1.6-m flat-to-flat, 70 mm thick segments). .... 230

Table 7-1 Altitude axis: summary of the design results ..... 255

Table 7-2 Azimuth axis: summary of the design results ..... 255

Table 8-1: Spectral Envelope of maximum Tip-tilt signal (mirror tilt) to be corrected by M6AM. On-sky tip-tilt is $\sim$ mirror tilt/20. ....	302
Table 8-2: SCAO Strehl ratio (%) with the visible wavefront sensor.....	302
Table 8-3: SCAO Strehl ratio (%) with the infrared wavefront sensor.....	302
Table 8-4: Requirements for the Calico- Mux development funded by Caltech and ESO.....	311
Table 8-5: Local Loop Characteristics.....	327
Table 8-6: Analog performance (Capacitive Sensor).....	327
Table 8-7: Characteristics of potential materials for thin shells.....	330
Table 8-8: Main characteristics of the OWL large DMs.....	333
Table 8-9: Essential characteristics of the VLT adaptive secondary mirror.....	333
Table 8-10: AO systems commissioned or under development. SPARTA support starts with MAD.....	338
Table 8-11: GLAO Ensquared Energy (%) in 50mas pixel over 6' FOV.....	346
Table 8-12: GLAO – Gain in Ensquared Energy in 50mas pixel over 6' FOV, corrected PSF vs. seeing.....	346
Table 8-13: GLAO Ensquared Energy variation in 50 mas pixel over FOV (PSF uniformity)...	346
Table 8-14. Field references.....	360
Table 8-15: MCAO performance (Strehl Ratio, %) over 1' FOV vs. seeing and NGS magnitudes;.....	366
Table 8-16: MCAO Strehl Ratio variation (in rms Sr) over the 1' FOV;.....	366
Table 8-17. Four technologies to achieve the XAO requirements.....	390
Table 8-18: Quantitative evaluation of the known LGS issues versus telescope diameter.....	397
Table 9-1: Design guidelines.....	409
Table 9-2: Kevlar available grades.....	424
Table 9-3: Main axes friction drive and bearing topology.....	433
Table 9-4: Load cases.....	433
Table 9-5: Main axes torque requirement.....	433
Table 9-6: Friction drive generated torque.....	434
Table 9-7: Cost breakdown of OWL's drive and bearing systems.....	434
Table 9-8: Maglev main requirements.....	435
Table 9-9. Bearings & drives linear generate forces.....	436
Table 9-10. Minimum required stiffness.....	437
Table 9-11: Telescope mass breakdown.....	448
Table 9-12: Mass moment of inertia.....	448
Table 9-13: Mass and inertia budget of the FE model in zenith configuration.....	450
Table 9-14: Differential rigid body motions of the optical elements due to gravity.....	452
Table 9-15: Worst case rigid body and PTV motions of M1 and M2 segments due to static wind.....	453
Table 9-16: Eigenfrequencies and effective masses of zenith configuration.....	458
Table 9-17: Eigenfrequencies and effective masses of 30 ° configuration.....	458
Table 9-18: Eigenfrequencies and effective masses of 60 ° configuration.....	458

Table 9-19: $1\sigma$ maximum piston displacement of M1 and M2 due to von Karman wind load spectra applied to complete mirrors area.....	467
Table 9-20: $1\sigma$ maximum displacements of M1 and M2 segments (part of the mirror area loaded).....	467
Table 9-21: Maximum stresses, safety margins and displacements or survival wind load cases.....	471
Table 9-22: High configuration.....	475
Table 9-23: Low configuration.....	476
Table 9-24: Design options, overall properties.....	478
Table 10-1: Adapter-rotator requirements for a set of representative instruments.....	483
Table 10-2: Adapter-rotator requirements for a set of representative AO Systems.....	484
Table 10-3: Adapter-rotator requirements for Active Optics.....	484
Table 11-1: Main sites characteristics.....	486
Table 11-2: Concrete and steel quantities.....	496
Table 11-3: Power consumption estimation.....	511
Table 11-4: Volume of earth to be removed to prepare the site.....	515
Table 12-1: Instrument Concept Studies.....	518
Table 12-2: Gain in photon statistics with telescope size.....	525
Table 12-3: Magnitude limits for point sources at 100m, 60m and 30m.....	529
Table 12-4: Magnitude limits (S/N=5) for 1 hour integration time for OWL and JWST.....	530
Table 12-5: Proposed wave-lengths set for the differential imager.....	543
Table 12-6: Characteristics of Earth-like planets used in the simulation.....	546
Table 12-7: Characteristics of Jupiter-like planets used in the simulation.....	546
Table 12-8: Main characteristics of SCOWL.....	555
Table 12-9: AO Requirements from Instruments <sup>*</sup> : seeing-reduced image quality desirable <sup>*</sup> ; high frequency monitoring of water content of atmosphere desirable.....	558
Table 12-10: Detector Array Requirement.....	559
Table 14-1: PWV (mm) statistics for Paranal (January - August 1998) and Chajnantor (January - September 1999) for satellite and ground based site monitor measurements of PWV...	579
Table 14-2: Site locations and information.....	579
Table 14-3: Typical IR Backgrounds at Paranal (mag/arcsec-2), from J. Cuby et al., The Messenger 101, p.3, September 2000. Note that K, L and M values include telescope background.....	584
Table 14-4: Average background at Paranal (mag/arcsec-2), from >4000 FORS1 exposures during Apr.-Sep. 2001, by F. Patat, UBVRI Night Sky Brightness at ESO-Paranal during sunspot maximum, The Messenger 115, March 2004.....	584
Table 14-5: 50-years horizontal ground peak acceleration (g units) with 10% probability of exceedence.....	585
Table 14-6: Soil characteristics for Paranal area (Site 1) and La Palma (Site II).....	587
Table 14-7: NCEP / NCAR Reanalysis datasets used.....	600
Table 14-8: ECMWF Reanalysis datasets used (ERA-15).....	600
Table 14-9: TOMS Aerosol datasets used.....	601
Table 15-1: Human access.....	608

Table 15-2 Sliding enclosure maintenance requirements .....	613
Table 16-1. Total estimated cost (incl. contingency and overheads).....	632
Table 16-2. Estimated human resource requirements, design phase. ....	633
Table A- 1. ELT Design Study - overview of the Work Packages.....	660
Table A- 2. Position sensors main specifications.....	660
Table A- 3. Position actuators, essential characteristics.....	662
Table A- 4. Function of merit, criteria and relative weights. ....	712
Table A- 5. Mandatory requirements.....	712
Table A- 6. Merit function; guidelines for ratings.....	714
Table A- 7. Optional corrector, optical prescription.....	717

# Index of figures

Figure 2-1. Using primary distance indicators to disentangle cosmological models. The plot shows the apparent magnitude difference relative to an empty universe of several cosmological models as a function of redshift. Regions of application for various methods of distance estimates with OWL are indicated. .... 56

Figure 2-2 Simulation of observations of Supernovae with OWL. The current data from ground and space observations are shown. These observations will allow to determine the cosmic SN rate, and help disentangle cosmological models (e.g. whether a “quintessence field” or a “phantom energy” exist)..... 57

Figure 2-3 Brief history of the telescope. Stars are refractors, asterisks are speculum reflectors and circles are glass reflectors. Some specific telescopes are named..... 60

Figure 2-4 Improvement in sensitivity of telescopes expressed in “equivalent diameter of a perfect telescope” =  $\sqrt{\eta D^2}$ , with  $\eta$  the telescope overall efficiency (the dashed line is an aid to the eye, not a fit). .... 61

Figure 2-5. Layout of the OWL observatory. .... 64

Figure 2-6. Layout of the baseline optical design. .... 66

Figure 2-7. Primary mirror geometry (3048 segments)..... 70

Figure 2-8. Secondary mirror geometry (216 segments)..... 71

Figure 2-9. Telescope structure, overall layout..... 72

Figure 2-10. Structural steel module..... 73

Figure 2-11. Friction drive ..... 73

Figure 2-12. First light results with MAD (laboratory conditions). Atmospheric turbulence is emulated with phase screens. Seeing 0.5 arc seconds, coherence time 5 ms, wavelength 2.2  $\mu\text{m}$ . Adaptive loop frequency 210 Hz. .... 77

Figure 2-13. PSD of turbulent wind speed in open air and inside VLT enclosure (no wind screen)..... 79

Figure 2-14. Sliding enclosure (courtesy CL-MAP)..... 80

Figure 2-15. Design phase, major milestones. .... 89

Figure 2-16. Phase C/D major milestones. .... 90

Figure 2-17. ELT Design Study, Work Breakdown Structure..... 93

Figure 2-18. ELT Design Study, overall schedule..... 94

Figure 2-19. Unit cost vs. quantity (industrial data)..... 99

Figure 3-1. Time needed to achieve the same S/N on diffraction-limited telescopes as a ratio to the time needed on a 100m, i.e. $t/t_{100}$ (note the background limited, $t/t_{100} \propto D^4$ , and shot noise limited, $t/t_{100} \propto D^2$ , regimes).....	112
Figure 3-2. (From Science Book) The theoretical diffraction limits ( $\lambda/D$ ) for 8m, 30m and 100m telescopes are plotted at three wavelength values corresponding approximately to the J, H and K infrared bands (horizontal bars). Also plotted are curves of projected angular size as a function of redshift for objects of various physical sizes (10pc, 50pc, 300pc and 1kpc) for two sets of cosmological parameters: $(\Omega_M, \Omega_\Lambda)=(0,0)$ and $(0.3,0.7)$ for the lower and upper curves respectively. ....	113
Figure 3-3. Observability of major emission lines with redshift. ....	114
Figure 3-4 Simulated image of a solar-type system at 10 parsec (32 light-years).....	117
Figure 3-5 (From Science Book) Synthetic Colour-Magnitude Diagram computed using constant star formation rate from 13 Gyr ago to the present. The age of the stars are coded in different colours. Labels indicate different evolutionary phases: BL - blue loop; HB - Horizontal Branch; RC – Red Clump; RGB – red giant branch; AGB – asymptotic giant branch; MS – main sequence. From [119]. ....	119
Figure 3-6 Simulation of the formation of the galaxies in the Local Group in a cold dark matter scenario, by Ben Moore, Zurich, astronomy and cosmology research group ( <a href="http://www.nbody.net">www.nbody.net</a> ). ....	120
Figure 5-1 : Project V-diagram. ....	140
Figure 5-2: Requirements breakdown. ....	141
Figure 5-3: Schematic example of functional breakdown. ....	142
Figure 5-4. OWL architecture example. ....	142
Figure 5-5: Phase A “open loop” design iterations .....	143
Figure 5-6: Block diagram of the OWL Integrated Model.....	146
Figure 5-7: Relationship between the height above the ground and the mean velocity .....	153
Figure 5-8: Model velocity-PSD close to the M1 segments .....	154
Figure 5-9: Force PSD averaged over three different areas.....	155
Figure 5-10: Instantaneous pressure field on M1.....	156
Figure 5-11: Comparison of PSDs obtained by CFD with model PSDs.....	156
Figure 5-12: JBO Lovell Radio Telescope with pressure sensors .....	157
Figure 5-13 : Pressure power spectrum on the reflector of the Jodrell Bank Telescope .....	158
Figure 5-14: Pressure PSD measured in a wind tunnel .....	159
Figure 5-15. Respective areas of action of active and adaptive optical systems as a function of the spatial and temporal frequency of the perturbations .....	159
Figure 5-16: VLTI-Vinci Optical path difference power spectrum and Kolmogorov model saturation for aperture distances larger than the outer scale $L_0$ (credit. E. di Folco, ESO 2004).....	160
Figure 5-17: Steel pipe exposed to sun radiation.....	162
Figure 5-18: Temperature evolution .....	163
Figure 5-19: Environmental conditions.....	163
Figure 5-20: Acceleration response spectrum (Telescope, MLE, 0.34 g, 1.5 % damping).....	166
Figure 6-1. Implied characteristics. ....	187
Figure 6-2. Mechanical implementation of different optical designs. ....	189
Figure 6-3. Baseline optical design (design No 1). ....	190

Figure 6-4. Ritchey-Chretien design (design No 2).....	190
Figure 6-5. Four mirror, spherical primary & flat secondary mirrors solution (design No 3).....	191
Figure 6-6. Four-mirror, conic M1 & M2 design (design No 4).....	191
Figure 6-7. Four-mirror solution; f/0.89 spherical primary mirror .	192
Figure 6-8. 5-mirror solution, f/1.42 spherical primary mirror.....	192
Figure 6-9. Baseline optical design, major dimensions.....	195
Figure 6-10. Baseline design, optomechanical implementation. ....	196
Figure 6-11. 4-mirror f/15 design, 60-m aperture.....	198
Figure 6-12. Optical test set-up for the testing of a convex, aspherical 8-m class mirror.....	200
Figure 6-13. 60-m four mirror design with f/0.75 parabolic primary mirror.....	200
Figure 6-14. Coaxial design with f/5 focus. Field of view 6 arc minutes, f/1.3 primary mirror...	201
Figure 6-15. Baseline design; Strehl Ratio vs field of view.....	202
Figure 6-16. Baseline design; rms spot size (arc seconds) vs field radius.....	203
Figure 6-17. RMS wavefront error (microns) vs field radius. ....	203
Figure 6-18. Point Spread functions at 0.5 microns. Box size 0.040 arc seconds.....	204
Figure 6-19. Ensquared energy at 0.5 microns. Scale: 100 microns = 0.0342 arc seconds....	204
Figure 6-20. Point Spread functions at 2.2 microns. Box size 0.200 arc seconds.....	205
Figure 6-21. Ensquared energy at 2.2 microns. Scale: 500 microns=0.171 arc seconds. ....	205
Figure 6-22. Distortion.....	206
Figure 6-23. Vignetting by M5 as a function of M5 diameter. ....	206
Figure 6-24. Possible set of baffles.....	207
Figure 6-25. Pupil mask (emissivity budget). The pupil mask covers all obstructed areas except the inter-segment gaps and tensioning ropes.....	209
Figure 6-26. Aberrated layer image. ....	213
Figure 6-27. Adaptive correction error (wavefront RMS) for 1 km conjugate defocus.....	214
Figure 6-28. Image quality of the pupil conjugation; field of view 1 arc minute diameter. ....	215
Figure 6-29. Image quality of the pupil conjugation; field of view 3 arc minutes diameter. ....	215
Figure 6-30. Image quality of the pupil conjugation; field of view 6 arc minutes diameter. ....	216
Figure 6-31. Spot diagrams, LGS at 90 km on-axis and 3 arc minutes off-axis. ....	217
Figure 6-32. Wavefront map, LGS at 90 km, 3 arc minutes off-axis.....	217
Figure 6-33. Model of the pupil for studying diffraction effects .....	218
Figure 6-34 PSF from the pupil presented above. The field of view is 1 arc second diameter, wavelength is 650 nm. Here and further: logarithmic scale. ....	219
Figure 6-35 Diffraction by the “spider”. PSF box size 0.72” .....	220
Figure 6-36 Diffraction by “missing” segments. PSF box size 0.72” .....	221
Figure 6-37 Diffraction by the ropes. PSF box size 0.72” .....	221
Figure 6-38. Mechanism of the formation of diffraction peaks (gaps): the grid factor (dots) is multiplied by the segment PSF. Left: without gaps; except for the central one all peaks of the grid factor fall into zeros of the segment PSF <sub>s</sub> . Right: with gaps; peaks no longer coincide with PSF <sub>s</sub> zeros.....	222
Figure 6-39 Diffraction by intersegments gaps of the primary (left) and of the secondary mirrors (right). Box size 0.72 arc seconds. ....	222

Figure 6-40 Intensity slice representation of OWL PSF between $10^{-5}$ and $10^{-7}$ . Most diffraction artefacts are apparent.....	223
Figure 6-41 Intensity slice representation of OWL PSF with 30nm and 56nm wavefront RMS residual segmentation piston, tip-tilt errors on two segmented mirrors.....	226
Figure 6-42. Segment unit product tree.....	227
Figure 6-43. Primary and secondary mirror segments distributions. ....	228
Figure 6-44. Primary mirror geometry, obscurations and intersegments gaps variation. ....	229
Figure 6-45. Primary mirror segment blank.....	231
Figure 6-46. Secondary mirror segment blank.....	232
Figure 6-47. Zerodur hexagonal cast. Courtesy Schott. ....	233
Figure 6-48. CTE homogeneity of Zerodur. Courtesy Schott.....	233
Figure 6-49. Thermo-mechanical figure of merit. ....	234
Figure 6-50. Precursor (left) and 1-m sintered SiC segment (right). Courtesy Boostec. ....	235
Figure 6-51. Segments optical quality (rms slope) specifications. ....	237
Figure 6-52. Segments optical quality (rms amplitude) specifications. ....	238
Figure 6-53. Interferogram of a LAMOST 1-m spherical segment prototype. Courtesy REOSC. ....	239
Figure 6-54. Segment deflection on axial support. Zerodur, thickness 70 mm.....	240
Figure 6-55. M4 aspherization profile.....	241
Figure 6-56. M4 slope difference with respect to best fitting sphere.....	242
Figure 6-57. High spatial frequency wavefront error, VLT primary mirror.....	243
Figure 6-58. M4 optical test set-up.....	244
Figure 6-59. M4 nominal interferogram, double pass. ....	244
Figure 7-1. Wavefront control - overall layout. ....	248
Figure 7-2 Wavefront Control Architecture for OWL.....	249
Figure 7-3 Block diagram of the closed-loop system.....	251
Figure 7-4 Normalized PSD of the wind loads applied to different height: altitude configuration.....	252
Figure 7-5 Frequency characteristics of altitude models for four different configurations.....	252
Figure 7-6 Frequency characteristics of azimuth models for two different configurations.....	253
Figure 7-7 Output sensitivity function as a a measure of both the rejection of perturbation and the robustness for the altitude axis.....	254
Figure 7-8 Output sensitivity function as a measure of both the rejection of perturbations and the robustness for the azimuth axis.....	254
Figure 7-9 PSD of tracking error on the main bearing (altitude axis 30 deg) – open-loop (dashed), closed-loop (solid).....	255
Figure 7-10 Main bearing (altitude axis) tracking error for 30 deg configuration.....	255
Figure 7-11 Left) bogie subjected to various forces-- Right) friction as a function of velocity..	256
Figure 7-12. Tracking a ramp reference signal in closed-loop. Left: slope 0.1 arcsec/sec stick-slip motion. Right: slope 0.5 arcsec/sec; stick-slip disappears.....	257
Figure 7-13 Block-diagram of bogie control system: feedback + feed-forward friction compensation strategy.....	258



Figure 7-14 Closed loop simulation of seven bogies (with friction compensation), one bogie is passive which exhibits small stick-slip motion, oscillations are induced on other bogies.	258
Figure 7-15 Closed-loop simulation of the altitude axis at 30 deg tracking a ramp reference signal with a slope of 0.1 arcsec/sec: left) no feed-forward friction compensation--right) with feed-forward friction compensation	259
Figure 7-16 Closed-loop simulation of altitude, 30-deg configuration	260
Figure 7-17 Wavefront error (tilt) on the sky- Altitude simulation: zenith configuration, main axis control with different wind loads applied to different levels	260
Figure 7-18 PSD of the wavefront error (tilt) on the sky	261
Figure 7-19 Wavefront error (tilt) after field stabilization correction as a function of the closed-loop bandwidth	261
Figure 7-20 Block diagram of the closed-loop control of M6: field stabilization	262
Figure 7-21 PSD of the corrected tilt wave front error on the sky	262
Figure 7-22 Simulation results: wavefront errors before and after correction, tilt motions of the M6 unit and the input torque applied to the unit	263
Figure 7-23. Field of View of the Shack-Hartmann sensors on M3 and M4.	268
Figure 7-24. Two types of lenslet and their projection onto the edge of the segments	272
Figure 7-25. Shape of the PSF for piston steps ranging from 0 to $\lambda/2$ .	272
Figure 7-26. Conceptual setup of a Modified Mach-Zehnder interferometer.	273
Figure 7-27. Mach-Zehnder signal profile for a piston step of $\pi/2$ and for different optical path differences between the two arms. Theoretical predictions are on the left hand side and experimental results on the right hand side.	273
Figure 7-28. Phase mask principle.	274
Figure 7-29. Signal obtained with a mechanical piston step of 230 nm.	274
Figure 7-30. Signal obtained with the diffraction image technique (courtesy A. Schumacher)	275
Figure 7-31. Signal obtained with the pyramid sensor for a piston step between square segments (courtesy S. Esposito)	275
Figure 7-32. Position and surface piston levels of the hexagonal subapertures on the piston plate used for the laboratory tests (A=0nm, B=18nm, C=50nm, D=325nm).	276
Figure 7-33. Phasing sensor signal from the multisegment phase plate without (left) and with (right) turbulence.	277
Figure 7-34. Sensor signals and fitted curves for one border for the two cases without (upper plot) and with (lower plot) turbulence. Note the change of the character of the signal : from an oscillating behaviour to smooth wings according to the function f.	278
Figure 7-35. ZEUS measurements: amplitude of te signals versus known piston steps without (a) and with a turbulent generator (b). Note the reduction of the amplitude of the fitted sine curve from 0.65 to 0.29.	278
Figure 7-36. Hough transform of the signal (left) and the detected lines (right).	279
Figure 7-37. Piston steps distribution: Initial (a) and after 6th loop (b). The grey scale is in nm.	280
Figure 7-38. Closed loop simulations. Gain 0.5. Initial wave front RMS = 322.5nm, final RMS = 12.7nm.	281
Figure 7-39 Indexation of the segments.	282
Figure 7-40. Indexation of the borders between the segments	283
Figure 7-41. The signal from the gaps obtained by a high-pass filtering (a), two spatial Fourier filters (b), and the filtered patterns for the secondary (c) and primary (d) mirrors.	286

Figure 7-42 Scheme of segment system configuration.....	287
Figure 7-43 PSD of wind load on one segment .....	288
Figure 7-44 Position error RMS as a function of control bandwidth of each actuator.....	288
Figure 7-45 Closed-loop position error PSD compared to open loop PSD.....	289
Figure 7-46 Closed-loop response of system--- closed-loop bandwidth: 10Hz .....	290
Figure 7-47 Closed-loop simulation ---- with AFC, closed-loop bandwidth 10Hz.....	290
Figure 7-48 Closed-loop simulation ---- with AFC, closed-loop bandwidth 5Hz.....	291
Figure 7-49 Reaction force on back structure and wind load on segment.....	292
Figure 7-50 PSD of wind load and reaction force and back structure.....	292
Figure 7-51 Seven segment configuration .....	293
Figure 7-52 Wind load force on seven segments.....	294
Figure 7-53 Seven segment closed-loop simulation: edge sensor readings and absolute position of the segments. ....	294
Figure 7-54: 3D view APE on the nasmyth platform .....	296
Figure 7-55: 3D view of the ASM .....	296
Figure 7-56: Conceptual design of the IM .....	297
Figure 8-1: M6 Adaptive Mirror located in the corrector structure of the telescope. ....	300
Figure 8-2: Single Conjugate Adaptive Optics concept.....	300
Figure 8-3: Limited corrected FoV due to anisoplanatism in the SCAO concept.....	302
Figure 8-4: Statistical distribution of the outer scale .....	303
Figure 8-5: Conjugation altitudes of the M6AM unit.....	303
Figure 8-6: Geometrical characteristics of the M6 Adaptive Mirror .....	304
Figure 8-7: Control scheme of the M6AM unit and interface with the active optics. ....	305
Figure 8-8: Transmission of the wavefront sensor pick-up dichroic.....	306
Figure 8-9: Defocus of the wavefront sensor versus field position .....	307
Figure 8-10: Technology concept of the WFS L3CCD detector.....	307
Figure 8-11: Quantum Efficiency with deep depletion enhancement in the red.....	308
Figure 8-12: OWL pupil dissector for the Shack Hartmann wavefront sensor .....	308
Figure 8-13: Shack Hartmann wavefront sensor concept.....	309
Figure 8-14: Pyramid wavefront sensor concept.....	311
Figure 8-15: SCAO Shack Hartmann or Pyramid Real-time architecture .....	312
Figure 8-16: Strehl vs. Magnitude for the SH-WFS (without RON), in K, H, J bands (top to bottom), for the good seeing model (left) and bad seeing model (right). Results are on-axis .....	313
Figure 8-17: VLT Planet Finder performance for different Readout Noise .....	313
Figure 8-18: Ensquared Energy versus pixel size (K-H-J; top to bottom), for good seeing (left) and bad seeing models (right). Bright stars are considered.....	314
Figure 8-19: Affect of anisoplanatism on the performance of the SCAO system, in K, H and J bands (top to bottom), in good seeing model (left), and bad seeing (right).....	314
Figure 8-20: Strehl vs. Magnitude for the IR PYR (without RON on the left, 5e- ron rms on the right), in K, H, J bands (top to bottom), for the good seeing model. Results are on-axis. ....	315

Figure 8-21: Long Exposure PSF with 10000 ph/subap/integ (bright NGS), for the K band (left) and J-band (right). Both pictures are on-axis. Stretch is logarithmic.....	315
Figure 8-22: EE vs. pixel size, in the K, H and J bands, good seeing, and bright guide star. ...	316
Figure 8-23: Shape for the DM during closed loop. The "spikes" near the telescope central obstruction, created by diffraction effects on the PYR WFS. ....	316
Figure 8-24: On-axis strehl versus wavelength for a bright reference star .....	317
Figure 8-25: Point Spread Functions obtained with SCAO. From left to right 2.2, 5 and 10 $\mu$ m. Good seeing conditions, bright on-axis star. ....	317
Figure 8-26: P-V DM mechanical stroke requirements versus spatial frequency for a seeing of 1.5" and different outer scales (Courtesy, T. Fusco-ONERA).....	318
Figure 8-27: Strehl (on-axis) vs. L0, for the SH based SCAO system (good seeing), in K, H and J bands .....	318
Figure 8-28: Conceptual design for the 1120mm diameter, 1170 actuators VLT deformable secondary mirror.....	322
Figure 8-29: Force/thin shell mirror (VLT design) based on Cold plate, Reference body & thin shell. A Hexapod, attached to the cold plate, provides fine focusing & centering (Courtesy, Microgate/ADS, Italy).....	322
Figure 8-30: Closer view of the actuator distribution on one half of the DSM (Courtesy Microgate/ADS) .....	323
Figure 8-31: Light weighting scheme of the VLT design Reference Body; estimated weight (Zerodur) is 27kg while a monolithic design would lead to 130 kg (Courtesy Microgate/ADS, Italy).....	324
Figure 8-32: Double side polishing device for flat shell. Six shells, maximum diameter of 68mm each can be polished at once (Courtesy SESO, France) .....	325
Figure 8-33: The successive steps of thin shell slumping (Courtesy INAF) .....	326
Figure 8-34: Scheme of internal control loop of actuator positions (left hand side). Feed-forward force added to the control schematic on the right hand side.....	327
Figure 8-35: Mode stiffness versus mode number for the VLT DSM.....	328
Figure 8-36: Theoretical Influence Function of a thin shell DM. Left: the IF (scale in mm), right: the associated stress in the glass (square grid of actuator at 29mm spacing, 2mm thick) .....	329
Figure 8-37. Permanent magnet mounted on the shell.....	330
Figure 8-38. Permanent magnet sizing .....	330
Figure 8-39: Shell thickness producing 15 nm rms gravitational sag (30nm rms wavefront error) vs. actuator pitch.....	331
Figure 8-40: Shell gravitational sag (nm) vs. act. pitch for Zerodur, ULE, Borosilicate, Steel & CVCSiC. ....	331
Figure 8-41: Shell deformation or stroke. Absolute analytical model accuracy: 50%; valid for relative material comparison.....	332
Figure 8-42: Optical diagram of the VLT Deformable Secondary Mirror test setup.....	334
Figure 8-43: Mechanical setup of the VLT deformable secondary mirror Test facility.....	335
Figure 8-44: Possible test setup for the OWL M6. In the case of spherical mirror a corrector is needed for aberration compensation (not shown here) .....	335
Figure 8-45: Quantum Efficiency curves of the L3 CCD and the PN-sensor.....	336
Figure 8-46: Pn-Sensor readout principle for the 256x256 detector.....	337
Figure 8-47: Left: Shack-Hartmann read-out; right: Pyramid read-out .....	341

Figure 8-48: SPARTA Architecture .....	342
Figure 8-49: Preliminary statistics of the turbulence profile at Paranal .....	343
Figure 8-50: Fraction of turbulence located at 200 m as measured by the SLODAR at Paranal .....	344
Figure 8-51: Ground Layer Adaptive Optics concept .....	344
Figure 8-52: GLAO real-time hardware architecture .....	347
Figure 8-53: Frequency of circular 6 arcmin diameter fields as a function of the number of NGS included at the North Galactic Pole for different NGS limiting magnitudes .....	349
Figure 8-54: Frequency of circular 6 arcmin diameter fields as a function of the number of NGS included on them at $l=0^\circ$ and $b= 50^\circ $ for different NGS limiting magnitudes. ....	349
Figure 8-55: Performance of the VLT MACAO system on UT4 .....	350
Figure 8-56: GLAO Ensquared Energy in 50mas for seeing of 0.53" (left) and 1" (right) at 0.5 $\mu$ m; 6 NGSs .....	350
Figure 8-57: Gain of EE in 50mas brought by GLAO relative to seeing for seeing of 0.53" (left) and 1" (right) at 0.5 $\mu$ m; 6 NGSs .....	350
Figure 8-58: EE vs field of view position (K-band); 3NGS in 3' plus 3 NGSs [3-6']; faint star 1e-/sub-aperture/s, good seeing model .....	351
Figure 8-59: Corrected PSF with GLAO using 6 NGSs, 6', good seeing (left) and bad seeing (right), K band, on-axis, 10ph / subap / NGS top curve is GLAO, bottom curve is the uncorrected seeing. ....	351
Figure 8-60: Effect of the outer scale of turbulence ( $L_0$ ) on the Strehl obtained with GLAO with 3 NGSs within 3' FOV; good seeing; Top to bottom: K, H, J. ....	351
Figure 8-61: HAWK-I concept based in CPU-only SPARTA architecture. With the new FPGA architecture the number of computational units will be reduced. ....	353
Figure 8-62: Concept of Multi-object Adaptive Optics or Distributed Adaptive Optics with wavefront sensors in open loop .....	354
Figure 8-63: MOAO concept with the wavefront sensor in pseudo closed loop .....	355
Figure 8-64: GLAO combined with MOAO concept with the wavefront sensor in open loop (right) and in pseudo closed loop (left) .....	356
Figure 8-65: MOMFIS schematic functional diagram (Courtesy LAM, France) .....	357
Figure 8-66: MOMFIS general view of the implementation: in the focal plane small pick-off mirrors are positioned with a robot, directing the target beams steering mirrors and the reference star beams to the WFS. The steering mirrors direct in turn the beam to the DM and IFU units (Courtesy LAM, France) .....	358
Figure 8-67: MOAO control loops .....	359
Figure 8-68: MOAO Real-Time Computer Concept. The diagram shows an example with only 4 wave-front sensors with local DM and 6 clusters each serving one IFU. The Dm on the right side is the M6AM. ....	360
Figure 8-69: Gain in Ensquared Energy in a 50 mas pixel for each scientific target, H band, 1" seeing. ....	361
Figure 8-70. Left: mean distance to the center of the field (arcmin) for the considered constellations. Right: integrated magnitude of all the used NGSs .....	361
Figure 8-71: Optical setup of SESAME (Courtesy LESIA) .....	362
Figure 8-72: General MCAO concept (left). Star Oriented MCAO concept (right). Each NGS wavefront is measured with dedicated WFS and the signals are recombined to determine the correction to be applied to each DM conjugated at different altitudes. ....	364
Figure 8-73: Opto-mechanical concept of ONIRICA (Courtesy INAF) .....	365

- Figure 8-74: Architecture for a SH-based MCAO system with reduced number of reconstructed modes. .... 368
- Figure 8-75: Frequency of circular 6 arcmin diameter fields as a function of the number of NGS included on them at the North Galactic Pole (left) and at an intermediate galactic latitude  $l=0^\circ$   $b=50^\circ$  (right) ..... 369
- Figure 8-76: Strehl (K-band) as a function of the NGS number distributed on a 6 arcmin FoV optimized in the central 1 arcmin. Solid line:  $M_v=5$ , dashed line:  $M_v=16$ , dashed-dotted line:  $M_v=17$ , dashed-dotted-dotted line:  $M_v=18$ . For each magnitude: top line on-axis, bottom line: off-axis. .... 370
- Figure 8-77: Strehl (on-axis) for the good seeing model, MCAO, 3 NGSs, 2' FOV, K, H, J (top to bottom),  $M_v=16$  corresponds to 5 photons/subap/frame..... 370
- Figure 8-78: Numerical simulations of MCAO correction (Strehl ratio in K band, H and J bands (top to bottom)) on a 6 NGS asterism ( $M_v=5$  (left plot) and  $M_v\sim 16$  (right plot)), the good seeing model ( $\sim 0.5''$  was used). Correction is optimized for a 1' FoV (diameter)..... 370
- Figure 8-79: Barycentre speed of a G2-V star due to the differential atmospheric refraction between the WFS effective wavelength and the instrument observing in K band for different target declinations ..... 371
- Figure 8-80: Barycentre speed of a B5-V star (top) and a M5-V (bottom) with respect to a G0-V star observed in J Band. The curves stop when the Zenithal distance is larger than  $60^\circ$ . ..... 372
- Figure 8-81: Mapping of the FoV for interaction matrix estimation in MCAO ..... 375
- Figure 8-82: The MAD bench installed in the ESO optical laboratory during testing..... 376
- Figure 8-83: Optical layout of MAD. .... 377
- Figure 8-84: Left: the SH WFS area during integration. Right: the LOWFS during final testing. .... 378
- Figure 8-85: Left: MACAO bimorph DM used for conjugation at 8.5 Km. Right: the multi layer turbulence generator MAPS. .... 378
- Figure 8-86: MAD first light SCAO closed loop..... 379
- Figure 8-87: MAD first light GLAO closed loop. Only one phase screen at 6 Km altitude has been used and the guide stars were located on a circle of 1.5' diameter. The FWHM reduction factor is  $\sim 2.5$ . .... 379
- Figure 8-88: Encircled energy gain in the first light GLAO closed loop. At the FWHM radius of the corrected image the gain is  $\sim 2$ . .... 380
- Figure 8-89: Common path XAO concept for EPICS..... 384
- Figure 8-90: Individual scientific channel path. .... 384
- Figure 8-91: 5-sigma detection level after differential imaging for 0.1 nm rms differential chromatic error before the coronagraph (circular average).  $\lambda = 1600$  nm. .... 385
- Figure 8-92: Residuals after dual imaging with a perfect coronagraph (left), and a double stage Lyot coronagraph with prolate apodization (right.) ..... 386
- Figure 8-93: AO correction of co-phasing residuals. Left: initial co-phasing errors. Right: best fit with DM2 (0.67 actuator separation). .... 386
- Figure 8-94: Residual left by best fit of DM<sub>2</sub>..... 387
- Figure 8-95: Cut in wave-front maps of Figure 8-102 and In Figure 8-94. Solid line: initial co-phasing errors (piston and tip-tilt, 20 nm rms). Dashed line: DM<sub>2</sub> fit. Dotted-dashed-line: residual error figure after correction by DM<sub>2</sub> (6 nm rms error residual of high spatial frequencies). .... 387
- Figure 8-96: Effect of co-phasing on coronagraphic image at 1600 nm (Circular average of 2D image). Solid line: PSF without coronagraph. Dashed line: Coronagraphic image with initial

co-phasing residuals of 20 nm rms. Dotted-dashed line: Coronagraphic image of residuals after AO correction (6 nm rms). .....	388
Figure 8-97: Strehl ratio versus wave-length.....	388
Figure 8-98: Theoretical point spread function after a perfect coronagraph. ....	389
Figure 8-99: Probability to find a NGS/Galaxy versus magnitude over 2' FoV. Top to bottom: Galactic plane, 180-20°, Galactic Pole .....	393
Figure 8-100: Performance (gain in EE compared to seeing) of a single on-axis LGS. Solid: on-axis, dash: off-axis. Top to bottom: K, H and J bands. The good seeing model was used (0.5"). .....	394
Figure 8-101: LGS MCAO performance (K-band). Tip - Tilt stars at LGS positions. ....	395
Figure 8-102: Pseudo Infinite Guide Star conceptual layout.....	398
Figure 8-103: Sky-Projected Laser Array Shack-Hartmann conceptual layout.....	399
Figure 8-104: Virtual wavefront sensor conceptual layout. ....	400
Figure 8-105: Variable wavefront sensor conceptual layout. ....	401
Figure 8-106: Basic principle of measuring atmospheric turbulence with phase shifting interferometry.....	402
Figure 8-107 Schematic arrangement of a multiconjugate correction with lasers and LPSI. ...	403
Figure 8-108: Fiber laser .....	404
Figure 8-109: CW Raman laser.....	405
Figure 8-110: Hollow Core Photonic Crystal fibre.....	405
Figure 9-1: locked rotor mode evolution.....	410
Figure 9-2: Rotating Mass evolution.....	410
Figure 9-3: 1997 design, rocking chair design I. ....	411
Figure 9-4: 1997 design, rocking chair design II. ....	411
Figure 9-5: 1998 design. Four petals design.....	412
Figure 9-6: 1999 design I. Decoupled M2 unit. ....	413
Figure 9-7: 1999 design II. Light rocking chair design. ....	413
Figure 9-8: 1999 design III. Cradle and bearings design. ....	413
Figure 9-9: 2000 design. Cradle and bearings design evolution.....	414
Figure 9-10: 2002 design. Cradle and bearings design evolution.....	415
Figure 9-11: 2004 design. Fractal design.....	415
Figure 9-12: OWL telescope structure. Side view.....	416
Figure 9-13: OWL telescope structure. Side view.....	417
Figure 9-14: Structural materials stiffness and strength.....	418
Figure 9-15: Typical welded node. ....	419
Figure 9-16: Base Fractal pattern.....	419
Figure 9-17: Base Module. ....	420
Figure 9-18: Node exploded view.....	420
Figure 9-19: Azimuth Structure .....	420
Figure 9-20: Azimuth structure and foundation interface .....	421
Figure 9-21: Altitude Structure .....	422

Figure 9-22: Top view..... 422

Figure 9-23: Sets of parallel rope..... 424

Figure 9-24: Rope mechanical interface..... 424

Figure 9-25: Wind vortex shedding..... 425

Figure 9-26: Cable damping system. (Courtesy of ULB). ..... 425

Figure 9-27: Active damping concept. (Courtesy of ULB)..... 425

Figure 9-28: Focal station layout..... 426

Figure 9-29: Focal station external dimensions. .... 427

Figure 9-30: Focal station external dimensions. Side view..... 427

Figure 9-31: Fibre fed focal station. .... 427

Figure 9-32: Axial and Radial Bogies..... 429

Figure 9-33: Bogie layout..... 429

Figure 9-34: Axial And Radial Bogies cross section. .... 429

Figure 9-35: Azimuth bogies location..... 430

Figure 9-36: Computer controlled hydraulic cylinders of the master bogies..... 431

Figure 9-37: Communicating vessels measurement..... 432

Figure 9-38: Bogies breadboard test setup..... 433

Figure 9-39. MagLev for trains ..... 436

Figure 9-40. OWL MagLev available design location. .... 436

Figure 9-41: Corrector..... 437

Figure 9-42: M6 lay out design and location ..... 438

Figure 9-43: M6 unit overall dimensions. .... 439

Figure 9-44: Optical bems intersection ..... 439

Figure 9-45: M6 available design volume. .... 440

Figure 9-46: Segment support system..... 441

Figure 9-47: Hexagonal segment assembly..... 441

Figure 9-48: Layout of WEB..... 445

Figure 9-49: WEB Functional Layout..... 445

Figure 9-50: Air conditioning layout..... 447

Figure 9-51: Inner ventilation. .... 447

Figure 9-52: FE Model of OWL in zenith configuration. .... 449

Figure 9-53: Side view of FE Model of OWL 60° from zenith. .... 450

Figure 9-54. Analysis tree flow chart..... 451

Figure 9-55: Vertical uz displacement distribution due to gravity for zenith configuration. Complete structure (left) and mirrors M1 to M6 (right). ..... 453

Figure 9-56: Displacement distribution due to gravity for 60° configuration. Complete structure in global vertical uz direction (left) and mirrors in normal displacements (right). ..... 453

Figure 9-57. Normal displacement distribution of optical elements under static wind at60°..... 454

Figure 9-58: Vertical z-displacement distribution due to uniform temperature change of 10° C. .... 455

Figure 9-59: Equivalent stress distribution due to temperature change of 10° C. ....	455
Figure 9-60: Temperature distribution due to sun radiation at 60° altitude angle. ....	456
Figure 9-61: Vertical (uz) displacement distribution due to sun radiation at 60° altitude angle. ....	457
Figure 9-62: Equivalent stress distribution due to sun radiation at 60° altitude angle. ....	457
Figure 9-63: Mode shape of first eigenfrequency in zenith configuration at 1.59 Hz. ....	459
Figure 9-64: Altitude locked rotor mode shape in zenith configuration at 2.58 Hz. ....	459
Figure 9-65: Azimuth locked rotor mode shape in zenith configuration at 2.86 Hz. ....	460
Figure 9-66: Piston mode of altitude and corrector structure at 4 Hz. ....	460
Figure 9-67: Piston mode of M2 unit structure at 7.3 Hz. ....	461
Figure 9-68: FE models of M1(left) and M2 cell (right) structures. respectively. ....	461
Figure 9-69: Piston mode of M1 Cell structure alone at 5.1 Hz. ....	462
Figure 9-70: Piston mode of M2 cell structure alone at 7.8 Hz. ....	462
Figure 9-71: Natural frequencies versus mode number. ....	463
Figure 9-72: Effective masses versus frequency. ....	463
Figure 9-73: 1σ normal displacement distribution of M1. ....	465
Figure 9-74: 1σ normal displacement distribution of M2. ....	465
Figure 9-75: 1σ response PSD of piston displacement of M1. ....	466
Figure 9-76: 1σ response PSD of piston displacement of M2. ....	466
Figure 9-77: 1σ response PSD of segments piston displacement of M1. ....	468
Figure 9-78: 1σ response PSD of segments piston displacement of M2. ....	468
Figure 9-79: FE-model and major dimensions of the OWL with foundation and soil. ....	470
Figure 9-80: Transfer function from wind load to y-deflection of M1. ....	471
Figure 9-81: SMITH diagram. ....	474
Figure 9-82: Base line. High configuration. ....	475
Figure 9-83: Low configuration. ....	476
Figure 9-84: OWL scaled down 60 meters. ....	477
Figure 10-1: Adapter Rotator. ....	479
Figure 10-2: Adaptor Rotator location. ....	480
Figure 10-3: Adapter Rotator section. ....	481
Figure 10-4: Adapter Rotator Instrument design volume. ....	482
Figure 10-5: Pickup mirror scan range. ....	482
Figure 11-1: Cargolifter building. ....	487
Figure 11-2: Baseline lay-out (courtesy CI-Map). ....	489
Figure 11-3: Top view of the enclosure and telescope foundations. ....	490
Figure 11-4: Principle scheme of natural cooling of the enclosure volume. ....	491
Figure 11-5 Simple thermal model of the enclosure. ....	492
Figure 11-6 Typical temperature evolution of the enclosure assuming site 5 m/s wind speed. ....	493
Figure 11-7 Enclosure opening cycle (courtesy CI-Map). ....	494



Figure 11-8: Enclosure foundations overview day park position (above). Night park position (bottom) .....	495
Figure 11-9: Typical reinforcement .....	497
Figure 11-10 Typical cladding panel .....	498
Figure 11-11: Main arch .....	499
Figure 11-12: Hinge (courtesy cl-MAP).....	499
Figure 11-13: Conceptual design of the drive system.....	500
Figure 11-14: Principle of the air supporting structure (courtesy Airlight).....	502
Figure 11-15: Lay out of the alternative design of the OWL enclosure.....	503
Figure 11-16. Two halves concept (right below teh VLT telescopes platform).....	503
Figure 11-17: Radome concept (cupola) for OWL (courtesy cl-MAP) .....	504
Figure 11-18: Radome concept using air cushion technology (courtesy AirLight).....	505
Figure 11-19 Arch-like structure fixing the arches holding the membranes.....	506
Figure 11-20 Airtensity concept radome enclosure open .....	506
Figure 11-21: Ventarrones (top right of the figure).....	507
Figure 11-22: La Palma.....	507
Figure 11-23: Horizontal in-line coating plant (courtesy SISTEC-It) .....	509
Figure 11-24: Ventarrones: Observatory lay out (auxiliary building side above; hotel side below) .....	514
Figure 11-25 The enclosure installed in La Palma.....	515
Figure 12-1. The CODEX concept. The simulation represents two observations of the Ly $\alpha$ forest of the same QSO taken at time $T_0$ (dotted line) and at time $T_0+10^7$ years (continuous ). CODEX/OWL will measure this effect for a separation of the two epochs as short as 10 years by comparing a large sample of high S/N QSO absorption spectra obtained with OWL.....	520
Figure 12-2. Expected wavelength shift for different cosmological models: Standard Cold Dark Matter (lower line. no cosmological constant) and $\Lambda$ Cold Dark Matter (middle line) with cosmological constant = 0.7. The upper line gives the difference of the two. The signature of the non-zero cosmological constant is the change in sign of the wavelength shift.....	521
Figure 12-3. Magnitude distribution of known brightest QSO's vs. redshift. From photon statistics and simulations of measurements in the Ly $\alpha$ forest at different redshift one derives the "iso-accuracy" curves plotted in the diagram. The required 1 cm/s/ accuracy is obtained with all the QSO below the 'iso-accuracy' curve in 2000 hours integration ( 80m telescope. total efficiency 14%. S/N= 13600). In reality the required statistics will be obtained by observing with shorter integrations different QSOs (~40) distributed over the whole sky and at different redshifts. ....	521
Figure 12-4. Optical Layout of one of the CODEX units. Each spectrograph is contained in a volume of ~3x2x1 meter. The 5 Units will be identical. ....	522
Figure 12-5. Statistics of photon arrival times in light beams with different entropies. Light may carry more information than that revealed by imaging and spectroscopy: Photons from given directions with given wavelengths give the same astronomical images and spectra. though the light may differ in statistics of photon arrival times. These can be "random". as in maximum-entropy black-body radiation (Bose-Einstein distribution with a certain "bunching" in time). or may be quite different if the radiation deviates from thermodynamic equilibrium. (Loudon: The Quantum Theory of Light. 2000). ....	524
Figure 12-6 Current optical concept for a QuantEYE detector head: a distributed detector array and a segmented aperture. The collimator-lens system magnifies 1/60 times (collimator	

focal length = 600 mm. lens focal length = 10 mm). giving a nominal spot size of 50 $\mu\text{m}$ for a 1arcsec source.....	525
Figure 12-7 The concept of the Hypertelescope .....	526
Figure 12-8: NIR C-M diagram from theoretical isocrones by Girardi et al. (2002. A&A 391.195) .....	528
Figure 12-9 The PSF radial intensity distribution as derived from MCAO assessment for the central field of ONIRICA at OWL and used in the simulation of photometry in crowded stellar fields .....	529
Figure 12-10 The limiting (S/N=5) magnitude $K_{(AB)}$ for point sources as a function of the exposure time .....	529
Figure 12-11 The limiting (S/N=5) magnitude $K(AB)$ for point sources as a function of the exposure time for OWL and the JWST (assuming same instrument and detector performance).....	530
Figure 12-12 Optical layout of ONIRICA (central field) .....	531
Figure 12-13: Concept of the channel splitting in ONIRICA. The FoV splitting is provided by a pyramidal mirror located at the intermediate focal planes.....	531
Figure 12-14: Sketch of a single unit of a Smart Fast Camera .....	532
Figure 12-15: The picture on the left illustrates the SFC concept in which the light of a wide FoV is divided by a lenslet array. ....	532
Figure 12-16: Opto-mechanical layout of ONIRICA including the two. wide and narrow. channels. The tubular trusses have the function to stiff the cryogenic tubes.....	533
Figure 12-17 Two views of the instrument envelope in the instrument bay .....	533
Figure 12-18 MOMFIS conceptual optical layout (see text).....	535
Figure 12-19. Overall MOMFIS implementation in the focal station.....	536
Figure 12-20. Illustration of the MOMFIS operation. Image Correction is performed locally along the line of sight of the target before image slicing and wavelength dispersion. ....	537
Figure 12-21. Contrast vs. angular separation for different types of planets. (Courtesy O. Lardiere).....	538
Figure 12-22: Number of stars versus distance from Earth for different spectral types.....	539
Figure 12-23: $\text{O}_2$ A-band at high spectral resolution. ....	541
Figure 12-24: EPICS will be composed of three spectral channels for the scientific instruments and one for wave-front sensing. ....	542
Figure 12-25: Differential Imager based on dichroics splitting the beam in 4 wavelengths. ....	543
Figure 12-26: Block diagram for the EPICS polarimetric mode concept.....	544
Figure 12-27: Optical scheme for the high precision polarimetric mode in EPICS .....	545
Figure 12-28: Example of halo intensity with perfect coronagraph after adaptive optics correction . Error sources: servo-lag. photon noise (30 % transmission + L3CCD noise excess in WFS). chromatic seeing. aliasing. fitting. static aberration (5 nm rms). ....	546
Figure 12-29: Minimum exposure time as a function of distance to detect at $5\sigma$ an Earth-like planet in the $\text{H}_2\text{O}$ band ( $1.25\mu\text{m}$ . $r_0=12.1\text{cm}$ . $\tau_0=10\text{mn}$ . Simple Differential Imaging. $0.08\mu\text{m}$ bandwidth. 0.44 atmospheric transmission) .....	547
Figure 12-30: Minimum exposure time as a function of distance to detect at $50\sigma$ a Jupiter-like planet in the $\text{CH}_4$ band ( $1.60\mu\text{m}$ . $r_0=12.1\text{cm}$ . $\tau_0=10\text{ms}$ . Simple Differential Imaging. $0.055\mu\text{m}$ bandwidth) .....	547
Figure 12-31. Rotation curve of the nucleus Seyfert 2 galaxy NGC 7582 (M. Wold. 2005). Circles: VLT-VISIR measurements using the $[\text{NII}]$ line at $12.8\mu\text{m}$ with a spatial resolution of $0.4''$ (40pc). Lines: models with different masses of the central black hole.....	549

Figure 12-32: Optical concept of one of the imaging-low resolution spectroscopy of T-OWL.. 550

Figure 12-33. Sensitivity of T-OWL as compared to other thermal infrared facilities for imaging of stellar-like sources..... 551

Figure 12-34. The effect of a “growing” telescope primary on the PSF . Each frame is a  $2 \times 2 \text{ arcsec}^2$  field with the resulting PSF. The columns from left to right correspond to year after year until completion of the OWL-. The rows are for three filling strategies: the top row is by starting with a 100m x 100m cross. the middle row is a ring-like geometry starting from the outside and the lower row is a ring-like geometry starting from the inside. .... 553

Figure 12-35: Dust mass detectable ( $10\sigma$ ) by SCOWL at  $450\mu\text{m}$  around nearby stars as a function of distance. The upper green line represents the mass of the dusty system  $\epsilon$  Eri. and the lower line the dust mass of our own Solar System. .... 554

Figure 12-36: SCOWL cryostat cross section..... 556

Figure 13-1: Structural nodes container..... 561

Figure 13-2: Pipe elements shipping..... 562

Figure 13-3: Azimuth tracks alignment metrology..... 563

Figure 13-4: Structural elements alignment..... 563

Figure 13-5: Azimuth tracks integration ..... 565

Figure 13-6: Azimuth Basement integration..... 565

Figure 13-7: Azimuth first floor integration ..... 566

Figure 13-8: Azimuth structure complete integration ..... 566

Figure 13-9: Altitude lower part integration. .... 567

Figure 13-10: Altitude M1 cell and central tower integration..... 567

Figure 13-11: altitude structure complete integration..... 568

Figure 13-12: Segment Support Structure. .... 569

Figure 13-13: Segments integration..... 570

Figure 13-14: Segment handling tool. notional design..... 570

Figure 13-15: Segment handling tool. notional design..... 571

Figure 13-16: Handling of segment on the extractor..... 571

Figure 13-17: Clamped and constrained segment..... 572

Figure 13-18: Un-clamped and un-constrained segment..... 572

Figure 13-19: Segment coarse pre-phasing ..... 573

Figure 13-20: Segment fine pre-phasing..... 573

Figure 14-1: Fraction of time that skies are clear (%) at night for the years 1999 and 2000 over Canaries, NW Africa and Southern Spain (A. Erasmus. ESO Interim Report. Oct. 2004) ..... 578

Figure 14-2: Locations of the sites in Chile, Bolivia and Argentina that were compared using satellite data. Contours show the topography at 500m intervals (see Table 14-2). ..... 580

Figure 14-3: PWV percentile values at each site under clear conditions..... 580

Figure 14-4: The Carlsberg Meridian Circle (CAMC) database at La Palma..... 581

Figure 14-5: Diurnal Atmospheric Extinction over Teide Observatory (Tenerife, Canary Islands). Ref: A. Jimenez et al.. Fig.4..... 581

Figure 14-6: Correlation of satellite UV and ground based V monthly averaged measurements CAMC AE>0.20. NIMBUS7 AE>0.2. Pixel center < 55km from ORM ..... 582

Figure 14-7: World map of jet aircraft contrails in 1992 (top). and predicted for 2050 (bottom). from [72].....	583
Figure 14-8: Seeing vs. local wind direction (0=North. 90=East etc.) and velocity at Paranal for best (right) and worst (left) observing conditions (2001-2004. over 778127 samples; J. Navarrete. ESO Observatory).....	584
Figure 14-9: Peak ground acceleration (PGA) that a site can expect during the next 50 years with 10 percent probability GSHAP (Global Seismic Hazard Assessment Project) .....	586
Figure 14-10: Site view.....	587
Figure 14-11: SLODAR Shack-Hartman pattern using narrow (left) and wide (right) binaries. ....	589
Figure 14-12: An example SLODAR determination of $r_0$ . Left: Measured Zernike coefficient variances. $\sigma_j$ (crosses) and the theoretical (Noll) fit (solid line). Right: Calculated value of $r_0$ versus WFS integration number (2ms CCD integrations at 190Hz).....	589
Figure 14-13 One-dimensional simulated cross-correlation (solid line) and autocorrelation (broken line) in the direction of the binary separation for a 24x24 sub-aperture.....	590
Figure 14-14: MASS principle. scintillation of a single star is measured through 4 concentric annular apertures.....	590
Figure 14-15: Relative contribution of the various atmospheric slabs to the integral of the turbulence obtained by combining SLODAR and MASS profiler data after reduction of the overlap area. The common database covers about 116 hours from February to August 2005.....	592
Figure 14-16: Complete atmospheric turbulence profile reconstructed from contemporaneous combined SLODAR and MASS measurements. ....	592
Figure 14-17: Observatorio Roque de los Muchachos (ORM). La Palma. Canary Islands. Spain ( <a href="http://www.otri.iac.es/sitesting/">http://www.otri.iac.es/sitesting/</a> ) .....	594
Figure 14-18: Morocco Anti-Atlas mountain area has the highest percentage of photometric nights along the North African continental west coast.....	595
Figure 14-19: Paranal North area proposes several candidate sites along what could become "the photon valley" of the 21st century .....	596
Figure 14-20: the Macon range. to the East of the huge Arizaro salt flat in NW Argentina allies high altitude (>4500m) and lower seismic activity ( <a href="http://www.iate.oac.uncor.edu/tolar/">http://www.iate.oac.uncor.edu/tolar/</a> ) 597	597
Figure 14-21: 20th century PDO "events" persisted for 20-to-30 years. while typical ENSO events persisted for 6 to 18 months.....	598
Figure 14-22: Monthly statistics of photometric nights at Paranal and La Silla and their relation to El-Nino Southern Oscillation Index.....	599
Figure 14-23: Monthly statistics of seeing at Paranal and La Silla and their relation to El-Nino Southern Oscillation Index.....	599
Figure 14-24: The FRIOWL user interface.....	602
Figure 14-25: DIMM seeing (1mn average) versus contemporaneous UT1 Cassegrain Active Optics Image Quality (atmospheric dispersion corrected) estimates for January-August 2005 (compilation. J. Navarrete. Paranal). ....	603
Figure 14-26: UT1-UT2 comparison of contemporaneous Cassegrain Active Optics Image Quality (atmospheric dispersion corrected) estimates for January-August 2005 (compilation. J. Navarrete. Paranal). ....	604
Figure 14-27: ISAAC. K (lower graph) and H (upper graph) band zenith image quality as measured (dots) and as expected from DIMM after outer scale correction following [63]; M. Casali. I.R. image quality at the VLT. ESO Internal Report. 02 June 2005.....	605
Figure 15-1: Accessibility.....	609
Figure 15-2: Corrector integration route.....	609

Figure 15-3: M6 unit integration route ..... 610  
Figure 15-4: M6 unit integration route inside the corrector ..... 610  
Figure 15-5: M6 unit integration access ..... 611  
Figure 15-6: Primary mirror cover docking operation..... 612  
Figure 15-7: Covers on Primary mirror..... 612  
Figure 15-8 lifting platform for inspection and maintenance of cladding..... 614  
Figure 15-9: OWL horizontal parking configuration. .... 614  
Figure 15-10: Secondary mirror handling facilities..... 615  
Figure 16-1. ESO Management structure. .... 621  
Figure 16-2. OWL organizational structure. .... 626  
Figure 16-3. High level schedule..... 631

Figure A- 1. Allocated volume for the Position sensors (Glass ceramic blanks). .... 661  
Figure A- 2. Allocated volume for the Position sensors (Silicon Carbide blanks)..... 661  
Figure A- 3. Position actuators. Implementation and design volume..... 662  
Figure A- 4. WEB 0° layout (zenith), side view. .... 663  
Figure A- 5. WEB 60° layout, front view. .... 663  
Figure A- 6. Block-Diagram of APE..... 664  
Figure A- 7. APE optical design; the telescope focus is at the bottom of the figure. PWFS:  
Pyramid WaveFront Sensor; BS: Beam Splitter; ASM: Active Segmented Mirror. .... 665  
Figure A- 8. 1-m silicon carbide BOOSTEC blank prototype. .... 667  
Figure A- 9. Friction drive breadboard ..... 668  
Figure A- 10. Optional two-mirror corrector ( $f/2.1$  focus, 4 arc minutes total field of view)..... 715  
Figure A- 11. Optional corrector; Strehl Ratio vs field radius..... 716  
Figure A- 12. Optional corrector; RMS spot size, RMS wavefront error vs. field radius..... 716