



THE EUROPEAN ELT

- A project lead by ESO on behalf of 14 member states
 - 42m adaptive telescope with segmented primary based on a 5-mirror design
- In Phase B since Jan 2007
 - Goal of Phase B: Proposal for construction by 2010
- Schedule:
 - Detailed design phase until end 2010
 - External reviews: Mid-term (May 2009), construction (Sep 2010)
 - Start of construction: 2011
 - First light: 2018
- Cost
 - Telescope + 1st gen instruments: ~ 950 million Euros
 - Operations (incl new instruments, overheads): ~ 50 M€/year
- Resources
 - 2007-2009: 57.2 M€ (including 110 FTEs)
 - 2008-2011: 5 M€ for E-ELT related R&D
 - Supporting activities from FP6 (28.8 M€) & FP7 (6.1 M€)

+ES+ 0 +


PHASE B STATUS

- Phase B extended to December 2010
- Mid-term review
 - Passed 12-13 May 2009
- All major telescope subsystems undergoing first or second iteration through industrial suppliers
 - Several reached preliminary design and are moving to next
 - > FEED studies ongoing
- All Phase A instrumentation studies ongoing
 - ▶ 8 instruments, 2 post-focal AO modules
- Operations scenarios being analyzed
 - Observing modes
 - > Logistics, maintenance, safety
 - Operations costs evaluated
- Progress of DRM and DRSP
- Site Selection Advisory Committee



HISTORICAL BACKGROUND

- Precursor (1977): 25m telescope ideas (Meinel et al)
- ELTs as we conceive them today have been around since the late 80s, early 90s: Swedish 25-m telescope
- mid 90s: OWL 100-m & CELT 30-m
- Early 00s: Euro-50, VLOT, GSMT, CELT, OWL, GMT
- In 2004 ESO Council resolved that:
 - ESO's highest priority strategic goal must be the European retention of astronomical leadership and excellence into the era of Extremely Large Telescopes...
 - the construction of an Extremely Large Telescope on a competitive time scale will be addressed by radical strategic planning, especially with respect to the development of enabling technologies and the exploration of all options, including seeking additional funds, for fast implementation



ELT effort re-oriented at the end of 2005 towards "the best affordable ELT Facility that can be built on a competitive timescale and with acceptable risks"

Mid 00s: consolidation to E-ELT, TMT & GMT



GUIDELINES

- -Affordable
 - Cost ~ VLT, ALMA
- -Timely

JWST (2014) synergy, competitors



-Acceptable risk

No essential items R&D on critical path Upgrade paths where appropriate



THE DRIVER

Planets in other stellar systems

- Imaging and spectroscopy
- -The quest for Earth-like exo-planets

Stellar populations


- In galaxies inaccessible today (e.g. ellipticals in Virgo cluster)
- Across the whole history
 (i.e. extent) of the Universe


Cosmology

- –The first stars/galaxies
- -Direct measure of deceleration
- Evolution of cosmic parameters
- -Dark matter, dark energy

The unknown

-Open new parameter space








ELT SCIENCE CASE DEVELOPMENT IN EUROPE







BRIEF HISTORY OF THE TELESCOPE: WHY BREAK A TIME HONORED TRADITION? DETECTORS HAVE IMPROVED MORE THAN DIAMETERS





THE SCIENCE CASE: THREE PILLARS

- Contemporary science: Today's clever ideas | the DRM
- Synergy with other facilities:











8-10m telescopes

ALMA


JWST


LSST

SKA


• Discoveries: Opening parameter space (photon sensitivity, spatial resolution)











VLT

~50 m²

25 mas

1µm:

GMT

~400 m² 9 mas

~600 m² 7 mas

(With thanks to Markus Kissler-Patig and Isobel Hook)



Key Contemporary Science (1)

Exo-planets / planet- and star-formation

Direct detections of rocky planets in habitable zones

 Characterisation of Exo-planet atmospheres

Pre-biotic molecules






Key Contemporary Science (2)


Understanding the formation and evolution of

galaxies


 Imaging and spectroscopy of resolved stellar populations in galaxies

 Black holes and AGN (Active Galactic Nuclei)













Key Contemporary Science (3)

Fundamental physics

- Variation of fundamental constants (α,μ)
- Direct measurement of the expansion of the universe
- Test of General relativity around black holes











Key Contemporary Science (3)

Fundamental physics


- Variation of fundamental constants (α,μ)
- Direct measurement of the expansion of the universe
- Test of General relativity around black holes







- 42m E-ELT on Macon: sky = -2 mag/arcsec
 - Star: G2V, d = 5pc Planet: mass = 4 M_{box} age = 5 Gyr, a = 4AU



- MIDIR: PAH2-filter (λ =11.25μm, Δλ=1μm) Strehl ratio = 93%, seeing = $0.70 \cdot 0.75$ arcsec


Observed Velocity Variation of Gliese 58:

Orbital Phase


- How common are systems like ours?
- How do planetary systems form?
- **Direct Detection**
 - Spatial resolution with ExAO: ~ 10⁹ contrast required for Earth-like planets
 - Mid-IR direct detection (contrast reduced but larger PSF)
- Radial velocity method (HARPS legacy)
 - Potential to reach lower-mass planets
 - ELT provides required collecting area
 - cm/s precision required for Earth-like planets
- Atmospheres
 - High resolution NIR spectroscopy of transiting planets

Direct detection of a "Super Earth"

 Simulations including systematic effects (e.g. speckles)




Speckle subtraction technique AB Dor, VLT/ SINFONI (Thatte et al 2007)




Simulated image courtesy of **EPICS** team. 10 hours, J band - PRELIMINARY

Direct detection of a "Super Earth"

 Simulations including systematic effects (e.g. speckles)




Speckle subtraction technique AB Dor, VLT/ SINFONI (Thatte et al 2007)




Simulated image courtesy of **EPICS** team. 10 hours, J band - PRELIMINARY

Watching the Universe accelerate in real time



- What is the Dark Energy?
- E-ELT can measure acceleration directly, in real time
- Fundamentally different probe (dynamical vs geometrical)
- Weak signal: ~ cm/s/yr. Requires:
- ELT (collecting area)
- 20 year monitoring campaign
- Ultra-high stability, high-resolution spectrograph (CODEX)




J. Liske et al., MNRAS, 2008 and Final DRM report

$$\dot{z} = \frac{dz}{dt} = (1+z)H_0 - H(t_e)$$

Measuring the redshift drift requires:

- Many photons, high resolution, extremely stable spectrograph
- ~20 yr long spectroscopic monitoring campaign

Best place to observe the redshift drift: the Lyman- α forest.




$$\dot{z} = \frac{dz}{dt} = (1+z)H_0 - H(t_e)$$

Measuring the redshift drift requires:

- Many photons, high resolution, extremely stable spectrograph
- ~20 yr long spectroscopic monitoring campaign

Best place to observe the redshift drift: the Lyman- α forest.




$$\dot{z} = \frac{dz}{dt} = (1+z)H_0 - H(t_e)$$

Measuring the redshift drift requires:

- Many photons, high resolution, extremely stable spectrograph
- ~20 yr long spectroscopic monitoring campaign


Best place to observe the redshift drift: the Lyman- α forest.




Simulations:

4000 hours over 20 years will deliver any one of these sets of points.


Different sets correspond to different target selection strategies.








SCIENCE → REQUIREMENTS: 1. SENSITIVITY




2. HIGH SPATIAL RESOLUTION





AN AO MILESTONE: MAD



MCAO: 3 Guide stars at 2'

K-band, FWHM: 100-120mas, Sr: >20%

0.7" seeing, Exposure 360 s

ISAAC seeing: ~ 0.5"




MCAO: 2 Guide "stars" (satellites Europa and Io)

2.14µm + 2.16µm filters

90 mas resolution (300 km at Jupiter)




AN AO MILESTONE: MAD



MCAO: 3 Guide stars at 2'

K-band, FWHM: 100-120mas, Sr: >20%

0.7" seeing, Exposure 360 s






MCAO: 2 Guide "stars" (satellites Europa and Io)

2.14µm + 2.16µm filters

90 mas resolution (300 km at Jupiter)






E-ELT TOP LEVEL REQUIREMENTS

- Diameter: ≥42m (area ≥ 1200 m²)
- Alt-Az, F/15 to F/18, fully steerable (0-360,0-90). Operational ZD: 0-70
- Adaptive telescope
- GLAO correction (≥ 5 arcmin, 90% sky, 80% time)
 - better than 2x FWHM improvement for median seeing conditions
- Post-focal: SCAO, MCAO, LTAO, ExAO, MOAO, ...
- Science field of view:
- 10 arcmin unvignetted. Diffraction limited by design
- 5 arcmin unobscured by guide probes
- Wavelength range: 0.3 24 µm
- Transmission @Nasmyth:
- > 50% at > 0.35 μ m, > 60 % at <math>> 0.4 μ m, > 70% at 0.7 μ m, > 80% at > 1 μ m
- Focal stations
- Two Nasmyth (multiple instruments, including gravity invariant option)
- At least one Coudé
- Fixed instrumentation (fast switching: < 10 min same focus, < 20 otherwise)



SUMMARY: POWERFUL PERFORMANCE





wavelength [µm]






PROGRAMME ORGANIZATION









TELESCOPE

Optical design

- novel 5 mirror concept (3 mirror anastigmat + 2 flats)
- diffraction limited over full 10' FoV
- flat, almost telecentric FoV
- "zoom" capability (Nasmyth, gravity invariant, coudé foci)
- laser "friendly" (very low aberrations even at zenith)








Telescope mount

- Two cradle solution
- Two industrial contracts concluded
- FEED ongoing
- Confirm cost and schedule
- Excellent stiffness (≥3Hz)







YEVIRON HO TIE Almospheric 68 |-Seq. Thermal Manuf. |-Seg Thermal Variations | Seg. Thermal result Fluid thermal M2 Demail()


themistAN: theroailets is

Swmal Mt cell

Bernal Structure -

CONTROL SYSTEM

- Technology identified
 - Error budget defined
- Testing at VLT, GTC




Zenth - On Axis


45 Deg - On Axis


45 Deg - If Off Arts






~ ANALYSIS





M1 Segment Support 155,000 elements 389,000 nodes

Subsystems and local FE Models





M2 cell contract ongoing M2 mirror offers received M2 Unit FEED tendered



THE MIRRORS





1m prototype

M4

Two industrial studies will deliver working prototypes





prototype actuator



M5


Deliverable of industrial electromechanical study: scale 1 prototype 4 mirror studies "heavy" option considered





DOME, ADAPTER

Two preliminary design contracts concluded FEED ongoing












Adapter rotator LGSs and NGSs WFSs in a single unit. Contract ongoing





INSTRUMENTATION PHASE A STUDIES












Possible instruments locat

ACRONYM (P.I.)	INSTRUMENT TYPE		
EAGLE (J.G. Cuby)	Wide Field, Multi IFU NIR Spectrograph with MOAO		
EPICS (M. Kasper)	Planet Imager and Spectrograph with XAO		
MICADO (R. Genzel)	Diffraction-limited NIR Camera- AO assisted		
HARMONI (N. Thatte)	Single Field, Wide Band Spectrograph - AO assisted		
CODEX (L.Pasquini)	High Spectral Resolution, High Stability Visual Spectrograph		
METIS (B. Brandl)	Mid Infrared Imager & Spectrograph -AO assisted		
OPTIMOS (F.Hammer,- O.LeFevre)	Wide Field, Visual, MOS (fibre or slit-based)- AO assisted?		
SIMPLE (L. Origlia)	High Spectral Resolution NIR Spectrograph -AO assisted		
	POST-FOCAL AO MODULES		
MAORY (E. Diolaiti)	Multi Conjugate AO module (high Strehl, field up to 2')		
ATLAS (T. Fusco)	Laser Tomography AO Module (high Strehl, narrow field		







SIMPLE

Science detector requirements as of end of phase 1

	Pixels	Detector type	Comments
OPTIMOS	4× [2× (4k×12k)] 4 channels a 2 arms	1/2 CCDs, 1/2 HgCdTe 15 µm pixels	DIORAMAS concept fast camera profits from concave detectors
CODEX	4kx4k blue + 6kx6k red	CCDs (blue/red sensitive) 15 µm pixels	fast camera profits from concave detectors
EPICS	5× (4k×4k) + ×	HgCdTe + CCD	+ detectors for the Extreme AO system
MICADO	16k×16k + 4k×4k	HgCdTe (<0.8-2.5 µm)	if 4k×4k, then 4-edge butting desired
HARMONI	8× (4k×4k)	HgCdTe 15 µm pixels	
SIMPLE	6kx2k or 12kx4k	HgCdTe 15 µm pixels	
EAGLE	10× (4k×4k)	HgCdTe 15 µm pixels	+ detectors for AO system
METIS	4x (2kx2k) + 5x (1kx1k)	HgCdTe 18 µm pixels Aquarius 30 µm pixels	NIR and mid-IR
ATLAS	6x (1kx1k) LGS + 1x (256x256) NGS	CCDs HgCdTe	used for LGS and NGS wavefront sensing
MAORY	6x (IkxIk) LGS + 3x (256x256) NGS	CCDs HgCdTe	used for LGS and NGS wavefront sensing



CONCLUSIONS

- The E-ELT is in the detailed design phase
- The Phase B is proceeding well
 - On time and in budget.
 - Passed its midterm review.

Consolidation with industry:

- Mitigation of cost and schedule uncertainties.
- 90% of telescope subsystems are in the industrial study pipeline.
- Final costing based largely on firm fixed price offers for construction.

Financing

- 1/3 of construction budget in ESO's projections < 2020 (all < 2035)
- Options to find the other 2/3 being discussed by ESO's Council
- Operations budget is included in long term projections

If approved, construction will take seven years

- First light possible in 2018